



QUIK Server

Installation manual

Version 12.1



Contents

1. General statements	3
1.1 Components of QUIK system	3
1.2 Technical requirements	4
1.3 License management on QUIK servers	4
2. Installation and configuration.....	6
2.1 QUIK server installation and configuration	6
2.2 QUIK Administrator installation and configuration	26
2.3 QUIK workstation banner configuration	44
2.4 File transfer settings	46
3. Running QUIK server	46
3.1 QUIK server launch parameters.....	47
4. Password encryption	50
5. Appendix.....	50
5.1 Format of positions	50
5.2 INI file conversion rules when migrating software from Windows to Linux.....	52
5.3 OpenSSL encryption configuration file format.....	54
5.4 MP encryption configuration file format	55
5.5 Daily maintenance of QUIK server	61
5.6 List of QUIK server error codes.....	67


You may email your comments on this Manual to: quiksupport@argatech.com



1. General statements

1.1 Components of QUIK system

QUIK software is implemented on the basis of 'client-server' technology. Data exchange between the server and user terminals is carried out by means of the Internet and/or a local network. The server provides the connection of information sources (trading systems, news flows and other) and processing of client orders. Client applications are designed for displaying the information and entering of customers' orders.



The central part of QUIK software is **QUIK Server** having the logical core and **interfaces** to connected elements (exchange interfaces and other information sources, data storage). The modular concept of connection allows accumulating the system's capacities when necessary by equipping the basic configuration by new features.

The interaction with **database** is realized through a special interface to ease changing of the used type of **DBMS**. The database is used to store information with a storage period of more than one day - registration data of users and rights to work with the system, as well as logs of executed operations.

Information received from the exchange trading systems is processed in RAM and not entered to the database. For a quick recovery in situation of failure the received data the cached on the disk in form of binary file is used. All work with the database is carried out through the dedicated database server.

The **access server** is connected to the principal QUIK server, receives data and distributes it to users according to their rights. The **access server** is used to handle a large number of user connections as it allows reducing the load on the principal system server.

Administration of the complex is carried out from the **QUIK Administrator** program unifying all the settings used by the logic core of server. For monitoring over the current state of the server and client connections the terminal **QMonitor** is used.

1.2 Technical requirements

The system and software requirements table is available on [the official website of QUIK](#) for the following:

- QUIK Server;
- Trading interfaces;
- News and market data interfaces;
- Service modules;
- Workstation of the administrator QUIK Administrator;
- Monitoring workstation QMonitor;
- Other modules and gateways to other exchanges.

The minimum requirements are listed on the website. It is recommended to consult with the QUIK Technical Support on the technical requirements, for example, if you intend to:

- Serve a large number of users;
- Connect a large number of gateways;
- Use the QUIK server for the market maker tasks or high-frequency trading.

1.3 License management on QUIK servers

The licensing includes the right to connect one copy of the application (plugin, technologic or client module) to a QUIK server. Applications of one type are included in a license pool.

If the broker uses several QUIK servers, the total number of licenses within the license pool, which is distributed among them using the data synchronization service (the Replicator program), is controlled.



After the maximum number of available licenses is reached, a corresponding diagnostic is written to a server log file. If no licenses are available for the plugin, the message "Not enough licenses!" appears in a QUIK workstation.

The applications for which license management is supported:

- Q2Q adapter;
- FIX adapter program interface (accounts);
- FIX adapter program interface (transactions);
- FIX Drop Copy program interface;
- FIX Client Connector program interface;
- Market Data Export Module;
- Level 2 Quotes export module;
- QUIK workstation for mobile devices (PocketQUIK);
- CoLibri SM risk manager terminal module;
- CoLibri FM risk manager terminal module;
- CoLibri FX risk manager terminal module;
- Specialized multi-broker service workstation;
- FX Convertor;
- BasketTrading module;
- Option analytics module;
- Asset manager terminal module (TrustManager);
- webQUIK workstation;
- QORT2QUIK adapter;
- Position management program interface.



2. Installation and configuration

2.1 QUIK server installation and configuration

2.1.1 DBMS configuration

1. Create a database on **SQL** server to be used by QUIK server.

To obtain the actual scripts for creating database, contact QUIK technical support: quiksupport@argatech.com, +7 (383) 219-16-06.

2. Open to edit **quik.ini** file in **quik\server** catalog with QUIK Server settings.

The file must be in Windows-1251 encoding.

In the [DB] section of this file configure the following parameters instead of the **file** parameter:

```
server=<name_of_SQL_server>,<port>
base=<DB_name_QUIK>
```

Example of the configured connection to SQL Server instance:

```
[DB]
server=SqlServerInstance,1234
base=QUIKDB
```

3. Configure the following parameters in section [DB]:

- **db_connect_timeout** – time of waiting for connection of QUIK Server to the DB server (in seconds). Range of valid values: from 1 to 600. Value by default: 60.
- **AuthMode** – used type of authentication on MS SQL server. Valid values:
 - login (by default) – use login and password specified in 'user' and 'password' parameters (the password can be [encrypted](#));
 - domain – use domain authentication.

If AuthMode=domain, the 'user' and 'password' in section [DB] are ignored and may be not specified.

- **Driver** – name of a driver which is used to connect to the QUIK server database. Valid values:



- _ ODBC Driver 17 for SQL Server (by default) – used to operate MS SQL Server 2014, 2016 or a newer DBMS (from the list of supported ones). Link to download the driver installation file from the official Microsoft website:
<https://go.microsoft.com/fwlink/?linkid=2223304>;
- _ PostgreSQL ANSI(x64) – used to operate PostgresPRO. Link to download the driver installation file from the official PostgreSQL website:
https://ftp.postgresql.org/pub/odbc/versions/msi/psqlodbc_13_02_0000-x64.zip;

When operating MS SQL Server, ODBC Driver 17 for SQL Server must be installed. When operating PostgresPRO, the psqlODBC driver version 13.2 or newer must be installed.

Example:

```
[DB]
server=<SQL server name without "tcp:" prefix>,<port>
Driver=ODBC Driver 17 for SQL Server
AdditionalParameters=MultiSubnetFailover=True;Network Library=DBMSSOCN
db_connect_timeout=120
```

- _ **AdditionalParameters** – setting to specify additional parameters for connecting to the DBMS. Value by default: "" (empty).

When connecting to the MS SQL cluster, set [MultiSubnetFailover](#)=True.

```
AdditionalParameters=MultiSubnetFailover=True
```

To connect to the PostgresPRO DBMS using a port other than a default one (5432), specify it in the AdditionalParameters parameter. For example:

```
AdditionalParameters=port=5431
```

- _ **SSLMode** – secure connection mode. Supported only when configuring a connection to the PostgresPRO DBMS. Valid values:
 - _ "" (empty, by default) – connection without encryption;
 - _ require;
 - _ verify-ca;
 - _ verify-full;
 - _ disable;
 - _ allow;
 - _ prefer.



For the description of secure connection modes, see the official website of PostgreSQL: www.postgresql.org/docs/current/libpq-ssl.html.

If the parameter is not set, the CertFileName, CertPKeyFileName, CertPass and CertCAFileName parameters are ignored.

- **CertCAFileName** – path to the file container of certificates of certification authorities. Value by default: "" (empty). Supported only when configuring a connection to the PostgresPRO DBMS.
- **CertFileName** – path and name of the secure connection certificate file. Value by default: "" (empty). Supported only when configuring a connection to the PostgresPRO DBMS.
- **CertPKeyFileName** – path and name of the secure private key file. Value by default: "" (empty). Supported only when configuring a connection to the PostgresPRO DBMS.
- **CertPass** – password for the private key file of the secure connection. Value by default: "" (empty). Supported only when configuring a connection to the PostgresPRO DBMS. The password must not start with \$ and #. The password can be [encrypted](#).

4. In section [DB], configure the possibility of receiving unread messages of the previous trading days:

- **messages_delivery_period** – number of days for which messages are loaded. Value by default: 0 (load only messages for the current trading day).

5. In section [db_module], configure the database provider being used:

- **driver** – the name of the executable file of the database provider. Value by default: "" (empty). Valid values:
 - For MS SQL – set the value "quik_db_ms.exe";
 - For PostgresPRO – set the value "quik_db_pg.exe".

Example of sections for MS SQL DBMS:

```
[DB]
server=MSSQL_SRV
base=QUIK_DB
user=sa
password=password
db_connect_timeout=30
AuthMode=login
Driver=ODBC Driver 17 for SQL Server
AdditionalParameters=MultiSubnetFailover=False;ApplicationIntent=ReadWrite

[db_module]
module=dstubrc.dll
driver=quik_db_ms.exe
```

Example of sections for PostgresPRO DBMS:




```
[DB]
server=PostgreSQL_SRV
base=QUIK_DB
user=sa
password=password
Driver=PostgreSQL ANSI(x64)
SSLMode=verify-full
CertCAFileName=Certs/root.crt
CertFileName=Certs/user.crt
CertPKeyFileName=Certs/user.key
CertPass=secret

[db_module]
module=dstubrc.dll
Driver=quik_db_pg.exe
```

2.1.2 Copying files

1. Create the catalog for installation of QUIK system (hereinafter <quik_dir>).
2. Copy there **astsgate**, **quikadministrator**, **front**, **keygen**, **quiktools**, **server** catalogs from <inst_dir> (directory with files for installation).

2.1.3 Creating a key for QUIK server

Using the **KeyGen** program create public and secret keys that will be later used by QUIK server (see keygen.pdf – User’s manual for keygen.exe).

1. To configure the parameter ‘Name of key holder’ type the name of organization in format “Name (identifier)”, for example:

```
Test-Invest (testinvest)
```

2. The identifier in parentheses will be then used to configure the system, call it <name_of_quik_server>.
3. Remember the password provided to protect the key. Call it <password_of_server_key>.
4. Copy the secret key of server (program KeyGen.exe saves file a:\secreg.tsk by default) to catalog <quik_dir>\server. For convenience in further work rename it to secrserv.tsk.
5. Copy the public key of server (program KeyGen.exe creates file a:\pubring.tsk by default) to catalog <quik_dir>\keygen. For convenience in further work rename it to <name_of_quik_server>.tsk. This key will be used by all users of the server with the software package **KeyGen**.



6. Open to edit file <quik_dir>\keygen\crypto.cfg and specify identifier of organization as value of parameter IMPORT:

```
IMPORT=<name_of_QUIK Server>
```

7. Using the **KeyGen** program create public and secret keys for manager of QUIK server (see keygen.pdf – User’s manual for keygen.exe). In step 3, the program prompts you to select file with public key of the system – select <name_of_quik_server>.txk file. Select the public key of the server in the list of keys (in the example that is “Test Invest (testinvest)”). Select the checkbox “Record and use skipping this step” to allow your users to avoid unnecessary operations subsequently when forming keys.

2.1.4 Registration in Windows services

1. Install the QUIK Server and the gateway to trading system as services. For this, type the following in the command line:

```
<quik_dir>\server\quik.exe -install  
<quik_dir>\tradesystemgate\tradesystemgate.exe -install
```

2. Open **controlpanel\services** and check if there are records identifying services of QUIK Server (identifier is “Quik Update Information Kit”), and gateway to trading system.
3. Create groups that are required to work in QUIK system:

Name	Group description
Quik	Users of this group have access to start the QUIK server (<quik_dir>\server\quik.exe)
Quik_source	Users of this group have access to start gateway to the trading system (<quik_dir>\astsgate\astsgate.exe)
Quik_ctl	Users of this group manage the QUIK server
Quik_stat	Users of this group can receive statistics on the QUIK server operation

4. Create a user-administrator giving him a name (for example <quikserv>) and password (for example <passwd>). Add this user to the groups created previously. Administrator of service on which the QUIK Server will work is also recommended to be added to these groups.
5. Configure services with identifiers “Quik Update Information Kit” and “Quik Transaction Gate” specifying the name and password to work in startup parameters of these services. For this select “Log on as:” and enter the administrator credentials of QUIK system – name <quikserv> and password <passwd>.



6. To use the domain authentication on MS SQL server, specify name of the domain user and password in startup parameters of the services.
7. Assign the users whose rights the services use with **Lock pages in memory** right. For this do the following:
 - Open the Start / Settings / Control Panel / Administrative Tools / Local Security Policy Windows menu item;
 - Open section Local Policies / User Rights Assignment.
 - In settings of the **Lock pages in memory** attribute, click the **Add user or group** button and add users to the list.

2.1.5 Currency and cross rates configuration

1. Run QUIK Administrator, select **QUIK server / Security classes** and add a class to the dictionary:

Parameter	Description
Currency cross rates	
Code	CROSSRATE
Description rus. / eng.	Currency cross rates
Settlement tag	
Class type	Currency cross rates

Only listed attributes should be enabled. Other attributes should be disabled.

2. On the computer where the QUIK server is installed, open the **quik.ini** file in the **quik\server** directory and edit it as follows:

- add a string (if not present) to [natural_level_section] section:

```
module=cur_module
```

- add strings in the end of the **quik.ini** file:

```
[cur_module]
module=dwcurg.dll
class_cfg=crossrate.ini
```

3. Open the **crossrate.ini** file in the **quik\server** directory and edit it as follows:

- specify for each currency code in [crossrate] section:



- _ currency full name;
- _ currency short name;
- _ accuracy of cross rate value;
- _ accuracy of cash position parameter values. Possible values are in the range [0, 8]. If the value is not explicitly specified, it is set as 2 by default.

Example:

```
[crossrate]
...
RUR=Rouble,Rouble,2
SUR=Rouble,Rouble,2
JPY=Japanese yen,Yen,6,0
```

NOTE:

If the accuracy of cash position parameter values for a currency differs from 2, all the interfaces, which are connected to the server, that transmit:

- _ this currency;
- _ instruments that are traded in this currency;
- _ currency pairs containing this currency;
- _ any monetary values expressed in this currency;

must support the transmission of monetary values with an accuracy that differs from 2, and an accuracy of a corresponding currency must be the same as se on the QUIK server. Otherwise, correct function of the system cannot be guaranteed.

For information about the transmission of monetary values with an accuracy that differs from 2 by a specific interface, contact QUIK technical support: quiksupport@argatech.com.

- _ specify each currency conversion rate in [crossrate_rate] section. As a rate value a free number can be used with the number of decimal places which does not exceed the **accuracy of cross rate value**, specified in the [crossrate] section (see as above).

For example:

```
[crossrate_rate]
RUR=1
SUR=1.00
JPY=0.627686
```

If you use cross rate for currencies, which are not specified in the [crossrate_rate] section, the corresponding error message will be displayed in the QMonitor program.

- _ specify in [main_currency] section:
- _ currency code. Value by default: RUR;
- _ currency symbol code in Unicode standard. Value by default: 0.

Currency codes are available by link:

https://www.unicode.org/charts/nameslist/n_20A0.html

- _ string with HTML code of a currency symbol in the format <Unicode-currency code>. If the code is specified in the 16-ary system, then add symbol 'x' before it. Value by default: "" (empty).
- _ Example:

```
[main_currency]
MAIN=RUR,20BD,8381
```

2.1.6 QUIK server parameters configuration

QUIK server parameters are configured in the following files:

- [crypto.cfg](#);
- [quik.ini](#);
- [trade_dates.ini](#);
- [settlement_dates.ini](#).

crypto.cfg file

For more information about the crypto.cfg file format, see the User's manual of the Software for creating and managing keys (KeyGen).

Open **crypto.cfg** file in catalog <quik_dir>\server\ and edit it as follows:

1. In [CryptoProviders] section specify the encrypting methods that are used (0 – disabled, 1 – enabled), for example:

```
[CryptoProviders]
openssl=1
```



2. In section, which corresponds to the encrypting method, selected on the previous step, specify full or relative paths to the executable and configuration files, for example:

```
[openssl]
Module=openssl_pr.dll
IniFile=openssl_pr.ini
```

3. Specify the following settings in the [auth] section:

```
[auth]
sign=secprov.dll
sign_provider=openssl      ; encryption method that is used for digital signature
```

quik.ini file

Open **quik.ini** file in catalog <quik_dir>\server\ and edit it as follows:

1. In section [dealer-library], configure the following parameters:

```
<code_of_your_firm_in_trading_system>=<relative path to setting file>
```

Example:

```
[dealer-library]
TEST_FIRM=.\dealer\testfirm.ini
```

2. In section [DB], configure the following parameters to access the database:

- _ **Server** – name of a server. Value by default: QDB1.
- _ **Base** – name of a database. Value by default: QUIK_DB.
- _ **User** – name of a database user.

A user must be included in the quik_server role in the QUIK server database.

- _ **Password** – password of a database user. A password must not begin with \$ and #. The password can be [encrypted](#).

Stop orders of users partially or completely blocked in QUIK Administrator (authorization is expired, the "Blocked" attribute is selected, authorization for markets is expired) can be also loaded from the QUIK server database at startup. Checking for blocked users and setting a period are managed by the quik.ini file settings:



- **stoporders.load_when_expired_la** – indicates of loading of stop orders for users with a general authorization expired as well as expired authorization for markets. Valid values:
 - 0 (by default) – stop orders of the users with expired authorization are not loaded;
 - 1 – stop orders of the users with expired authorization are loaded.
- **stoporders.mark_expired_as_foreign** – indicates of marking stop orders of the users with expired authorization by the “Foreign” attribute. The setting is used if stoporders.load_when_expired_la=1. Valid values;
 - 0 – stop orders of the users with expired authorization are not marked by the “Foreign” attribute;
 - 1 (by default) – stop orders of the users with expired authorization are marked by the “Foreign” attribute.
- **stoporders.expired_la_period** – number of days for loading stop orders of blocked users. Value by default: 14.

3. In section [Files], configure the following parameters:

- **EventsLogFileName** * – path and name of the main log file. Value by default: events.log.
- **ErrorsLogFileName** * – path and name of the errors log file. Value by default: errors.log.
- **DeallibLogFileName** * – path and name of the Limits calculation library log file. Value by default: Deallib.log.
- **DataFilesFolderName** – path to data files (.ik files). Value by default: .\.
- **LogFilesFolderName** – path to log files (events.log, errors.log, DB provider, deallib.log). Value by default: .\.

(*) If the parameter contains only log file name, the path specified in the LogFilesFolderName parameter is used.

4. In section [usend_module], configure the following parameters:

```
module=dwsend.dll
sysname=Information and Trading System QUIK "TestInvest" ; name of system displayed
in the informational window when connecting to server
name=testinvest ; server key
password=secret ; password to access the server key
port=15100 ; port number for user terminals connection
crypto_provider_ini_file=OpenSSL_Pr.ini; full or relative path to the encryption
settings file
connection_acceptance_tmo_ms ; timeout in milliseconds to wait for a new
connection. Valid values: from 0 to 60000. Value by default: 500
```

5. In section [ctl_module], configure the following parameters:



```
module=dwwqctl.dll
port=15120 ; port number for QMonitor connection
name=testinvest ; server key
password=secret ; password to access the server key
```

6. In section [time-set], specify the **hourshift** parameter if the server time is different from the gateway time:

```
hourshift=3 ; difference between the QUIK server time and the time of data
transmitted by the gateway, in hours
```

7. In section [mail], configure the following parameters of access to SMTP server:

```
Server=smtp.quik.ru ; Name or IP address of SMTP server
Port=25000 ; Port of SMTP server. Value by default: 25
User=test_user ; User name for authentication on SMTP server
Password=secret ; Password for authentication on SMTP server. A password must not
begin with $ and #. A password can be encrypted
FromAddress ; Sender address of emails related to two-factor authentication (and
password recovery)
```

8. In section [limits_module], configure the following parameters:

_ for mail distribution:

```
loadlimits_FromAddress=test@post.ru ; Address of message sender
loadlimits_mail_to=test1@post.ru ; Addresses of message receivers separated by commas
sign_settings_file=.\\qloadlimitx.ini ; Path to the QLoadLimitsX program settings
file for setting up clients' positions that QUIK server uses to load the limits file
signed by Bicrypt electronic digital signature
```

- _ **calclimit_old_stoporders** – attribute of blocking funds under stop orders of previous days. Valid values:
- _ 0 (by default) – do not block funds;
 - _ 1 – block funds.

For example:

```
calclimit_old_stoporders=0
```



The setting must not be used simultaneously with the Do not reserve actives for stop-orders on all of classes setting of Limits calculation library (for the setting description, see the Administrator's manual of Limits calculation library settings).

9. In section [trans_module], configure the parameters:

- **Change_wrong_single_clientcode** – the algorithm of client code change. The parameter is responsible for algorithm of substitution if the user has the only active client code. Valid values:
 - 0 – transaction is rejected with diagnostics 'Incorrect client code' if the client code does not match the user rights (Client specified the only code that does not match the rights. Or the client has two codes, one of them has an authorization expired and the client code in the submitted transaction does not match rights);
 - 1 (by default) – transaction is not rejected.

Example:

```
change_wrong_single_clientcode=1
```

- **trans_handling_privileged_users** – the list of users whose transactions are processed by the server regardless of the processing stage of these users' previous transactions.

The setting is applied after saving the configuration file, the server reboot is not required.

Format:

```
trans_handling_privileged_users=<list of UIDs, separated by commas>
```

Example:

```
trans_handling_privileged_users=100,200,300
```

10. In section [data_module], configure the parameter.

- **inactive_stops_lifetime** – maximum possible time in days from the last activation of stop order after which the stop order is cancelled. Values in range 1 to 13 are rounded to the minimum possible value – 14 days.
 - 0 – the setting is disabled;
 - 14 (by default) – minimum possible number of days (setting enabled).

Example:



```
inactive_stops_lifetime=14
```

- **news_days_keep** – duration of news storage on the server (in days). When the server is started, the news, the storage time of which exceeds the value specified in the parameter, are deleted from the storage. Value by default: 2.

If the replacement settings are enabled in the section (`firm_substitute = 1`, `client_codes_substitute = 1`), and the `codes.ini` or `firms.ini` files are empty or missing, the server crashes with an error:

Error reason	Diagnostics
codes.ini replacement file is missing	Configuration file "path-to-codes.ini" not found
firms.ini replacement file is missing	Configuration file "path-to-firms.ini" not found
codes.ini replacement file is empty	Configuration file "path-to-codes.ini" is empty
firms.ini replacement file is empty	Configuration file "path-to-firms.ini" is empty

- 11.**In section [Position], configure correspondence between alias of the firm (an alias used to replace a firm code with any other code to combine several firms into one within a unified cash position) from the Trading interface and firm code on the QUIK server with the unified cash position. The setting is relevant if the firm code of the trading interface and the unified cash position firm coincide. Alias is set by the trading interface when transmitting data on futures restrictions and positions of the unified cash position firm. Using the alias defines a type of account the data from the trading interface is intended for.

Format:

```
<alias firm with the unified cash position of Trading interface>=<code of firm with the unified cash position on QUIK server>
```

Example:

```
UNIFIED_FIRM=NC0038900000
```

Additional alias configuration is also required in section [Position] of MOEX Derivatives trading interface. Alias length must not exceed 12 characters.

- 12.**In the [data_pipe_module] section, configure the inbound / outbound replication of the date / time of the last login using the following settings:



- **disable_last_login_replication_in** – accept / not receive information about the date / time of the last login from the replicator. Default value is 0 (accept).
- **disable_last_login_replication_out** – send / not send information about the date / time of the last login to the replicator. Default value is 0 (send).

13. Set up two-factor authentication according to the section 2 of the Administrator's manual for the QUIK two-factor authentication.

14. Perform the setting of long order entry prohibition to prohibit or allow the user to submit orders with the "Good till date" / "Good till cancel" validity period to the trading system.

- Specify the following parameters in the [gtc-orders] section:
 - **markets** – list of markets in random order, separated by commas.
 - The **<Market>_classes** view parameters – classes of the market, which is specified in the parameter name, in any order separated by commas.
 - The **<Market>_expiration_mark_field** view parameters – name of the expiration attribute field for the market.
 - The **<Market>_expiration_date_field** view parameters – name of the expiration date field for the market.

Example:

```
[gtc-orders]
markets=MARKET1, MARKET2
MARKET1_classes=XXXXX,NNNNN
MARKET2_classes=YYYYY,MMMMM
MARKET1_expiration_mark_field=UseExpDate
MARKET1_expiration_date_field=ExpDate
MARKET2_expiration_mark_field=IMMCANCEL
MARKET2_expiration_date_field=EXPIRYDATE
```

An empty list of markets or classes in these markets means that the prohibition on entering long orders is disabled.

- In the **max_days_to_expire_order** parameter of the [calc-limits] section specify the maximum validity period of long orders in days, which will be valid for all classes of instruments listed in the **<Market>_classes** view parameters. Submission of an order that exceeds the **max_days_to_expire_order** limit will be terminated with an error.

If the "GTD/GTC orders" attribute is enabled in the user settings in the QUIK Administrator program, the max_days_to_expire_order parameter value will not affect the order validity period.



trade_dates.ini file

Open the **trade_dates.ini** file in the <quik_dir>\server\ directory and edit it.

In the [trade_date] section set up the exception dates for the calendar of trading and non-trading days used on the QUIK server. By default, from Monday through Friday are considered by the QUIK Server as trading days, and Saturday and Sunday as non-trading days. A day is considered to be a trading day if on this day there are trades in this QUIK server on any of the trading venues:

- If trading is planned on a weekday at least on one venue available on the QUIK server, then this date does not need to be added to the [trade_date] section.
- If on a weekday trading is not scheduled on any of the venue, then you need to add this date with the **holiday** attribute to the [trade_date] section.
- If trading is planned on a weekend on at least one venue available on the QUIK server, then you need to add this date with the **workday** attribute to the [trade_date] section.

The following parameters are set in the section:

- **ClearingTime** – session change time on the QUIK server in <HHMMSS> format. This point in time must be within the period when the QUIK server is stopped. Default value: 000000.
- **no_weekend** – attribute of the QUIK server operation in the **no days off** mode (Saturday and Sunday are considered working days). Valid values:
 - _ 0 (by default) – the QUIK server operation mode is determined by the standard calendar of working (weekdays) and non-working (weekends) days;
 - _ 1 – the QUIK server operates in the 7 days a week mode.
- Exclusion dates from the standard calendar, according to which the QUIK server is launched in the working or non-working day mode, in the format:

```
<YYYYMMDD>=holiday  
<YYYYMMDD>=workday
```

Where:

- _ **holiday** is non-working day;
- _ **workday** is working day.

See [note](#) for an example of how to fill in a section.

When starting the QUIK server with the [-holiday](#) or [-workday](#) launch parameters, section values have a lower priority.

settlement_dates.ini file

Open the **settlement_dates.ini** file in the <quik_dir>\server\ directory and edit it.

In the [settlement_date] section the exception dates are set for the calendar of settlement and non-settlement days used on the main trading venue. By default, from Monday through Friday



are considered by the QUIK Server as settlement days, and Saturday and Sunday as non-settlement days.

If a weekday is considered a non-settlement day on the main trading venue, then it must be added to the [settlement_date] section with the **holiday** attribute, and if a weekend is considered a settlement day, then it must be added with the **workday** attribute.

The described exception dates are applied to all trading modes, but have a lower priority than calendars set in the QUIK Administrator program. If a date is set in the [settlement_date] section as a holiday, but in the QUIK Administrator calendar as a working day, it will be considered as a working day.

The presence/absence of holidays results in the shift of the settlement date, which is indicated in the increase/decrease of calendar days between the trade execution and settlement when transactions with settlement codes other than T0 are performed, for example, T1, T2.

Filling in the [settlement_date] section has an impact on:

- Correct accounting of commission volume;
- Specification of the limit chain to which the blocking, crediting and debiting are applied;
- Identification of the last settlement period in the transaction limit chain for reports/trades for execution of the second part of REPO;
- Calculation of REPO term for non-negotiated and negotiated REPO modes and REPO with CCP;
- Accounting of ACI when calculating the blocked order volume on limits for REPO-M and REPO with CCP;
- Calculation of the trading system commission on deliverable SWAPs in the FX market which determines the start date of the first part of REPO;
- Specification of life period of GTD/GTC orders, including OMS orders, within which the maximum order volume is calculated considering dynamically adjusted ACI and bond face value, which affects the volume of blocked funds.

Section format:

```
<YYYYMMDD>=holiday  
<YYYYMMDD>=workday
```

Where:

- _ **holiday** is non-working day;
- _ **workday** is working day.

Examples for the [trade_date] and [settlement_date] sections:

Example 1

There are two interfaces on the server: to the Securities market of the Moscow Exchange and the Foreign securities market of the SPB Exchange. November 4, 2022 is a holiday that



is a non-settlement day on the Securities market of the Moscow Exchange, but trading on the Foreign securities market of the SPB Exchange.

You need to set the following settings.

```
[settlement_date]
20221104=holiday
```

Example 2

There is one interface on the server to the Securities market of the Moscow Exchange. November 4, 2022 is a holiday that is a non-settlement day on the Securities market of the Moscow Exchange. Thus, there is not a single trading mode on the server, in which trading will take place on this day.

You need to set the following settings:

```
[settlement_date]
20221104=holiday

[trade_date]
20221104=holiday
```

Example 3

There is one interface on the server to the Securities market of the Moscow Exchange. March 5, 2022 (Saturday) is a trading and settlement day.

You need to set the following settings:

```
[settlement_date]
20220305=workday

[trade_date]
20220305=workday
```

2.1.7 User distribution configuration

Catalogs <quik_dir>\front and <quik_dir>\keygen are intended for distribution to customers, so they are recommended to be copied to a separate place.

Catalog <quik_dir>\front contains the files of user's QUIK Workstation. If the QUIK Workstation version does not match the version in the <quik_dir>\front directory when a user connects to the server, the user will be offered an update. Therefore, current versions of the QUIK Workstation should be copied to the <quik_dir>\front directory for further updating by users.



The directory of the QUIK Workstation installation kit can be changed in the quik.ini file in the [areas] in the **frontend** parameter. The default setting value is areas\frontend.

A pair of access keys – public and secret ones must be generated for each new user registered in the system via the **KeyGen** program. Public key is registered via **QUIK Administrator**.

2.1.8 Block encryption configuration

Open to edit the file in catalog <quik_dir>\server\quik.ini and configure the following parameters in section [usend_module]:

- **enable_block_crypt** – indicates of block encryption. Valid values:
 - _ 0 (by default) – block encryption is not used;
 - _ 1 – block encryption is used.
- **block_crypt_size** – size of encryption block. Valid values: from 100 to 8192 (inclusively). Value by default: 1024.

2.1.9 Setting Limits calculation library asynchronous usage

If the parallel pre-trade and post trade control of operations with different orders is required to be set up, contact QUIK technical support: quiksupport@argatech.com for further instructions.

Firms to which asynchronous Limits calculation library usage is applied should be listed in the <quik_dir>\server\quik.ini file in the [dealer-library-async] section. For example:

```
[dealer-library-async]
NC0038900000
SPBFUT389
```

The following parameters can be set up in the [behavior] section:

- **numberofexecutors** – full number of queues of parallel processing of Limits calculation library algorithms for all the firms which use Limits calculation library asynchronously.
- **deallib.temppath** – file path to the directory for temporary storage of DLL copies for Limits calculation library.

For example:

```
[behavior]
deallib.temppath=.\temp
numberofexecutors=3
```



2.1.10 Exclusions for antivirus software

This section contains files and folders of the QUIK server that must be excluded from checking by antivirus software, as they are used during the server operation.

Files and folders to be excluded:

1. Folder with the QUIK server.

2. Folders and files specified in the server settings in quik.ini:

- paths to log files and .ik files that are specified in the [Files] section in the **LogFilesFolderName** and **DataFilesFolderName** parameters, for example:

```
LogFilesFolderName=.\logs  
DataFilesFolderName=.\data
```

- paths to the files of substitutions that are specified in the [data_module] section in the **firm_substitute_file** and **client_codes_substitute_file** parameters, for example:

```
firm_substitute_file=.\firms.ini  
client_codes_substitute_file=.\codes.ini
```

- paths to the archives that are specified in the [archive_module] section in the **ttp_dir** and **minutes_dir** parameters, for example:

```
ttp_dir=.\archive\minutes_ttp  
minutes_dir=.\archive\minutes
```

- path to the cross-rate settings that is specified in the [cur_module] section in the **class_cfg** parameter, for example:

```
class_cfg=crossrate.ini
```

- path to the crypto provider settings that is specified in the [usend_module] section in the **crypto_provider_ini_file** parameter, for example:

```
crypto_provider_ini_file=.\mp_pr.ini
```

- paths to the templates that are specified in the [quik_auth] section in the **TemplateRuRetrievingNotSupportedFileName** and **TemplateRuUnknownErrorFileName** parameters, for example:




```
TemplateRuRetrievingNotSupportedFileName=templates\ru\retrievingnotsupported  
templaterruunknownerrorfilename=templates\ru\unknownerror
```

3. Folders with the settings of crypto providers in the `crypto.cfg` file that are specified in the **IniFile** parameter, for example:

```
IniFile=mp_pr.ini
```

The net ports that are specified in the settings of server and access servers in the `quik.ini` file in the `port` parameter must be added to the exclusions.

2.1.11 Configuration of message text about termination of attorney power

The text of the message that is displayed when connecting with the keys of a user whose power of attorney to use the system has expired can be changed.

By default, the following text is displayed: "License expired".

The **licence_expired_text_*** setting allows changing the text sent when the attorney expires. The digit in the setting corresponds to the language identifier:

- `licence_expired_text_25` – message text in Russian;
- `licence_expired_text_9` – message text in English.

To change the message text, open the **server/quik.ini** file, in the `[usend_module]` section add the **license_expired_text_*** key and set the message text as its value, for example:

```
[usend_module]  
module=dwsend.dll  
licence_expired_text_9=License expired
```

2.1.12 Position rolling

The QUIK server can be launched in the mode of rolling clients' positions by money and instruments (stock market).

Before configuring position rolling, contact QUIK technical support for additional instructions: quiksupport@argatech.com.

To roll positions, do the configuration:



1. In the **quik.ini** file located in the <quik_dir>\server\ directory configure the following parameters:

- [data_module] section:
 - **rolling.rotation_depth** – rotation depth of files with positions located in the Backup directory. The server stores no more than the number of files specified in the setting for each type of position by money and by instrument. When the maximum value of the setting is reached, old files are deleted. Default value: 7.
 - **rolling.CPLimitTag** – tags separated by commas, which are used by the QUIK REPO Module to maintain limits for counterparties when rolling money positions. Only positions with settlement term T0 with the specified tags are considered. Default value: "" (empty).
- [calc-limits] section:
 - **UnifiedLeverageOnClient** – indicates that leverage of the same size is used in all cash positions of a client for whom **By discounts** or **MD+** margin lending scheme is used. Set the value 1. Default value is 0.

2. Start the server with the **-rolling (/ro)** launch parameter.

3. Connect the interface that will activate the positions after rolling.

The information of the transferred positions is updated only after the interfaces (trade interfaces or the Holiday Information interface) are connected.

2.2 QUIK Administrator installation and configuration

2.2.1 Installation and configuration of QUIK Administrator server part

1. To configure the database connection, install ODBC drivers for the OS.

For Windows OS:

- When connecting to MS SQL DBMS the ODBC Driver 17 for SQL Server ODBC driver must be installed on the computer where the qadminsrv service is installed. To check the driver availability, in the Windows menu enter the text "ODBC data sources" in the search box and open the appropriate window. Make sure that the Drivers tab in the list contains the driver with the following name: **ODBC Driver 17 for SQL Server**.

If there is no such driver, download the driver installation file from the official Microsoft website (<https://go.microsoft.com/fwlink/?linkid=2223304>) and install it on the computer where the service will be running.
- When connecting to PostgresPRO DBMS the PostgreSQL ANSI(x64) ODBC driver version 13.02 or newer must be installed on the computer where the qadminsrv service is installed. To check the driver and its version, run the odbcad32 utility in the Windows menu. Make sure that the driver with the **PostgreSQL ANSI(x64)** name and version 13.02 or newer is listed in the Drivers tab.

If there is no such driver, or the version is lower than expected, download the driver installation file from the PostgreSQL official website



(https://ftp.postgresql.org/pub/odbc/versions/msi/psqlodbc_13_02_0000-x64.zip) and install it on the computer where the service will be running.

For Linux OS:

1. Driver installation commands must be executed by a privileged user (root).
2. Internet access is required.

- _ To work with ODBC, install the libodbc1 and unixodbc packages using the following commands:

```
apt-get install libodbc1
apt-get install unixodbc
```

- _ Configure drivers for DBMS.

When connecting to the PostgresPRO DBMS, the libpq5 library must be updated to version 13.0 or newer on the computer where the qadminsrv service is installed.

- _ Run the following commands as a user with administrator permissions:

```
echo "deb http://apt.postgresql.org/pub/repos/apt buster-pgdg main" >
/etc/apt/sources.list.d/pgdg.list
wget --quiet -O - https://www.postgresql.org/media/keys/ACCC4CF8.asc | apt-key add -
apt-get update
apt remove libpq5
apt remove odbc-postgresql
apt-get install libpq5/buster-pgdg
apt-get install odbc-postgresql/buster-pgdg
```

If installation of packages from the official repository is unavailable, download files from the PostgreSQL repository and install them manually. For this, download the packages to the computer where the service is installed:

https://apt.postgresql.org/pub/repos/apt/pool//15/p/postgresql-15/libpq5_15.6-1.pgdg100+1_amd64.deb

https://apt.postgresql.org/pub/repos/apt/pool/main/p/psqlodbc/odbc-postgresql_16.00.0000-1.pgdg100+1_amd64.deb

Update the contents of the astra repository so that the package cache is consistent:

```
apt-get update
```

Remove old versions (if any):



```
apt remove libpq5
apt remove odbc-postgresql
```

These commands may terminate with an error, this does not affect further installation.

Install the downloaded packages:

```
dpkg -i libpq5_15.6-1.pgdg100+1_amd64.deb
dpkg -i odbc-postgresql_16.00.0000-1.pgdg100+1_amd64.deb
```

_ Make sure that a driver record has been added to the /etc/odbcinst.ini file:

```
[PostgreSQL Unicode]
Description=PostgreSQL ODBC driver (Unicode version)
Driver=/usr/lib/x86_64-linux-gnu/odbc/psqlodbcw.so
Setup=libodbcpsqlS.so
Debug=0
CommLog=1
UsageCount=1
```

If the record has not been added, add it yourself. Make sure that there is a file (the file name may differ depending on the version) at the path:

```
/usr/lib/x86_64-linux-gnu/odbc/psqlodbcw.so
```

2. Install the qadminsrv service.

For Windows OS:

- _ Copy all files from catalog <inst_dir>\qadminsrv\server to an arbitrary directory. The given catalog provides the **qadminsrv.ini** file containing the program settings.
- _ The <inst_dir>\qadminsrv\client\ catalog contains the client application of the program.
- _ To install the program, log in as a user with administrator permissions.
- _ Set the service name in the **qadminsrv.ini** file. For this, specify the appropriate values of the **name** and **displayname** parameters in the [Service] section.
- _ Run the command from the command line:

```
qadminsrv -install
```



For Linux OS:

The service is installed by a user with administrative privileges (root via the console by calling the run file <install_qadminsrv-xx.xx.xx.run>, where xx.xx.xx is the product version.

- _ Copy the install_qadminsrv-xx.xx.xx.run file to the directory that the current user has permissions to operate in, such as the home directory (/home/<user> or ~/).
- _ Execute the command to add execution rights to the run file:

```
sudo chmod +x ./install_qadminsrv-xx.xx.xx.run
```

- _ Execute the service installation command (qadminsrv – default name of the service to be installed):

```
sudo ./install_qadminsrv-xx.xx.xx.run -i [qadminsrv] [-d <rootdir>] [-n  
<srvusername>]
```

The service is installed to the /opt/arqasrv/quik/ directory. The following operations will be performed during the execution of the run file:

- _ If there is no system user arqasrv, it will be created with default permissions and included in the group with the same name. The /opt/arqasrv directory will be set as a home directory for this user. The service to be installed will work on behalf of this user.
- _ A subdirectory with the service name will be created in the /opt/arqasrv/quik directory, the distribution files of the software to be installed will be unpacked into this subdirectory.
- _ The arqasrv user will be assigned as the owner of all files and subdirectories in the service directory.
- _ A service named qadminsrv and running on behalf of the arqasrv system user will be registered in the systemd service management system.
- _ The .actions.log file will be created in the /opt/arqasrv/quik/qadminsrv directory, where the service installation process is logged.
- _ A file named qadminsrv will be created in the /etc/arqasrv directory to record the service installation parameters.
- _ Command files will be generated in the service directory to:
 - _ start the service, including with launch parameters: q_start.sh;
 - _ stop the service: q_stop.sh;
 - _ output of the current service status to the console: q_status.sh;
 - _ remove service: uninstall.sh;
 - _ convert configuration file names to lower case during migration: postmigration.sh.



If the service is successfully installed, the following message is displayed in the console: "Installation of service "qadminsrv" has been successfully completed".

In case of another diagnostic output, please contact the QUIK technical support: quiksupport@argatech.com.

Do not change the directory structure - moving or renaming may cause errors.

3. Configure the following settings in the `qadminsrv.ini` file:

- In section [Instances], specify configuration files of database connections in format:

```
<Port used for the given DB>=<Name of configuration file>
```

Example:

```
[Instances]
15301=cfg_broker1.ini
15302=cfg_broker2.ini
```

For Linux OS, perform conversions for the files that are added to the [Instances] section of the `qadminsrv.ini` configuration file according to the [INI file conversion rules when migrating software from Windows to Linux](#).

Parameters of connection with every database are described in a separate file.

- In section [Files], in the **Logs** parameter set the name of file for logging, if necessary.
- In section [General], edit the following settings, if necessary:
 - **MaxDeallibSize** – the maximum file size of the Limits calculation library settings to be saved to the Audit log. Value by default: 10485760 (the value in bytes corresponds to 10 MB).
 - **MaxDeallibSize_<Instance>** – the maximum file size of the Limits calculation library settings to be saved to the Audit log for the specified port (<Instance>). The value of the **MaxDeallibSize** setting is used as default.
 - **PathRelease** – path to the directory with update files of the QUIK Administrator client part. The path may be absolute or relative. Value by default for Windows OS: frontend\release\, for Linux OS: frontend/release/ (relative path from the QUIK Administrator server part directory).
 - **InactiveUserDisconnectTimeout** – indicates that a connection between the server and client parts of the QUIK Administrator program breaks when the user inactivity period in seconds, which is set in this setting, expires. If the value is 0, the setting is disabled. Default value: 900.



- **DisconnectWhenSessionLock** – indicates that a connection between the server and client parts of the QUIK Administrator program breaks when a session is blocked or a remote session is disconnected. Valid values:
 - 0 – a connection should not be broken;
 - 1 (by default) – a connection should be broken.

4. Configure the following settings in **<name of configuration file>.ini** server configuration file.

For Linux OS, perform conversions for all sections of the configuration file according to the [INI file conversion rules when migrating software from Windows to Linux](#).

- In section [DB] configure the parameters of access to the database:
 - **Server** – name of server.
 - **Base** – name of database.
 - **User** – name of a database user.

A user must be included in the quik_rbo and quik_auditor roles in the QUIK server database.

- **Password** – password of a database user. A password must not begin with \$ and #. The password can be [encrypted](#).
- **UsePersonalLogin** – to use personal logins for connection to the database specify the value 1.
- **AuthMode** – used type of authentication on MS SQL server. Valid values:
 - login (by default) – use login and password specified in 'user' and 'password' parameters (the password can be [encrypted](#));
 - domain – use domain authentication.

If AuthMode=domain, the 'user' and 'password' in section [DB] are ignored and may be not specified.

- **Driver** – name of ODBC driver which is used to connect to the QUIK server's database. Valid values:
 - ODBC Driver 17 for SQL Server – used when using MS SQL Server 2014, 2016 or a newer DBMS (from the list of supported ones);
 - PostgreSQL ANSI(x64) – used when using PostgresPRO;
 - "" (empty, by default) – used when using MS SQL Server 2012 or an older DBMS (from the list of supported ones).

If no setting value is specified, the "ODBC Driver 17 for SQL Server" is used.



When operating MS SQL Server, ODBC Driver 17 for SQL Server must be installed. When operating PostgresPRO, the psqlODBC driver version 13.2 or newer must be installed.

- 1. For Linux OS when creating DSN source for MS SQL driver the Server parameter is specified, and for PostgresPro driver the Servername parameter is specified.**
- 2. When working with PostgresPRO (Windows OS), the ANSI driver is used: Driver=PostgreSQL ANSI(x64)**
- 3. When working with PostgresPRO (Linux OS), the UNICODE driver: Driver=PostgreSQL Unicode**

- **Port** – port to connect to the PostgresPRO server. Value by default: 5432.
- **AdditionalParameters** – setting for specifying additional parameters of the DBMS connection. Value by default: "" (empty).
- **SSLMode** – secure connection mode. Supported only when configuring a connection to the PostgresPRO DBMS. Valid values:
 - "" (empty, by default) – connection without encryption;
 - require;
 - verify-ca;
 - verify-full;
 - disable;
 - allow;
 - prefer.

For the description of secure connection modes, see the official website of PostgreSQL: www.postgresql.org/docs/current/libpq-ssl.html.

If the parameter is not set, the CertFileName, CertPKeyFileName, CertPass and CertCAFileName parameters are ignored.

- **CertCAFileName** – path to the file container of certificates of certification authorities. Value by default: "" (empty). Supported only when configuring a connection to the PostgresPRO DBMS.
- **CertFileName** – path and name of the secure connection certificate file. Value by default: "" (empty). Supported only when configuring a connection to the PostgresPRO DBMS.
- **CertPKeyFileName** – path and name of the secure private key file. Value by default: "" (empty). Supported only when configuring a connection to the PostgresPRO DBMS.
- **CertPass** – password for the private key file of the secure connection. Value by default: "" (empty). Supported only when configuring a connection to the PostgresPRO DBMS. The password must not start with \$ and #. The password can be [encrypted](#).

Example:




```
[DB]
Server=QSERV
Base=QBROKER
User=login
Password=secret
UsePersonalLogin=1
AuthMode=login
Driver=ODBC Driver 17 for SQL Server
AdditionalParameters=MultiSubnetFailover=False;ApplicationIntent=ReadWrite
SSLMode=verify-full
CertCAFileName=Certs/root.crt
CertFileName=Certs/user.crt
CertPKeyFileName=Certs/user.key
CertPass=secret
```

- Set personal logins in section of [DataBaseLogin_<random text>] view if parameter **UsePersonalLogin=1**. Any number of sections may be specified.
 - **User** – login to work with database;
 - **Password** – password to work with database. A password must not begin with \$ and #. The password can be [encrypted](#);
 - **Users** – list of identifiers of users who can use the login. To establish a connection with server part of QUIK Administrator identifier must be also set in the configuration file of sub-broker access.

To connect to the QUIK Administrator server, the identifier must also be specified in the subbroker_template.tmpl file intended for setting up the sub-broker mode in the QUIK Administrator program. For the subbroker_template.tmpl file description, see sub-section 1.2 of the Administrator's manual for QUIK Administrator (for sub-broker).

- In section [Connect] configure the parameters of authorization:
 - **Name** – key identifier;
 - **Password** – password for the key. A password must not begin with \$ and #. The password can be [encrypted](#);

Example:

```
[Connect]
Name=KEY
Password=secret
```

- In section [QuikOptions] specify the following parameters:



- **RSASKeysInTransReport** – the mode of displaying RSA keys of user in report on transactions. Valid values:
 - 0 – RSA keys of user are not displayed in report on transactions;
 - 1 – all RSA keys of user are displayed in report on transactions;
 - 2 – only RSA keys not revoked for the moment of transaction registration are displayed in report on transactions.
- **ClientCodeDelimiter** – delimiter used when setting up the “Code on the dealer’s side” list in the rights by classes in the user editing dialog. Value by default: “,” (comma).
- **FirmId** – list of firms (separated by commas) available for selection in the Firm code field in the rights by classes in the user editing dialog.
- **UserExpireCheckDays** – number of days before the user’s authorization expires, when the notification starts. Value by default: 5.
- **ServiceUserExpireCheckDays** – number of days before the expiration of service user’s authorization, when the system notification starts. Value by default: current value of **UserExpireCheckDays**.
- **Title** – additional title of the QUIK Administrator program. Displayed after User UID.
- **PINCodesInTransReport** – feature of displaying PIN codes used for the Quik two-factor authentication type in the transaction report. Valid values:
 - 0 (by default) – PIN codes are not displayed in the transaction report;
 - 1 – PIN codes are displayed in the transaction report.
- **EnableMultiple2FaLogins** – attribute of using the same login for multiple users for the Active Directory two-factor authentication type. Logins are set in the Logins for another authorization system dictionary in QUIK Administrator. Valid values:
 - 0 (by default) – a login can only be used by one user;
 - 1 – the same login can be used for multiple users.
- **UsersCountThreshold** – the number of entries in the Users dictionary of the QUIK Administrator program at which the dictionary is split into pages containing the number of entries set in the **PageSize** parameter. Value by default: 10000.
- **PageSize** – the number of entries on a page in the Users dictionary of the QUIK Administrator program. This parameter is used, if the number of dictionary entries set in the **UsersCountThreshold** parameter is reached. Value by default: 100.

5. Configure the following settings of **crypto.cfg** file in first who strings without the section title:

- **PUBRING** – value: quik.dwq;
- **SECRING** – path to file with secret key.

Example:

```
PUBRING=quik.dwq
SECRING=secring.txk
```



6. To create a QUIK Administrator new account and assign a user with administrator's permissions, run QUIK Administrator server part using the key **-set-admin-right**. For details, see [2.2.3](#).

2.2.2 Authentication settings for QUIK Administrator

Configuring authentication in the QUIK Administrator program using the MP and OpenSSL cryptographic libraries.

1. In **qadmin.ini** (for client) and **qadminsrv.ini** (for server) specify settings of crypto providers to be used for authentication by login/password or for authentication in ActiveDirectory domain (not supported for Linux OS):

- _ In the [CryptoProviders] section specify available providers:
 - _ **openssl** – indicates that OpenSSL provider is used. Valid values:
 - _ 0 – provider is disabled;
 - _ 1 – provider is enabled;
 - _ **mp** – indicates that MP provider is used. Valid values:
 - _ 0 – provider is disabled;
 - _ 1 – provider is enabled.
- _ In the [CryptoProvidersSettings] section in the **CipherCryptoProvider** setting specify the default provider. Valid values:
 - _ **openssl** – default provider – openssl;
 - _ **mp** – default provider – mp_pr (used for Windows OS only).

If the key is absent the Qrypto32 provider is used by default.

- _ When the openssl provider is used specify its settings in the [openssl] section:
 - _ **module** – path to the provider's module. Value by default for Windows OS: openssl_pr.dll. Value for Linux OS: libopenssl_pr.so.
 - _ **inifile** – path to the provider's settings file. Value by default: openssl_pr.ini.
- _ When the MP provider is used specify its settings in the [mp] section:
 - _ **module** – path to the provider's module. Value by default: mp_pr.dll.
 - _ **inifile** – path to the provider's settings file. Value by default: mp_pr.ini.

2. Specify the setting of provider for client in openssl_pr.ini or mp_pr.ini depending on provider in use: in the [TLS Connection Settings] section in the **UsedHandShakeScheme** parameter set up the authentication scheme number. Valid values:

- _ 1 – authentication by certificate;
- _ 2 – authentication scheme by domain login and password through the Domain Controller (supported only if the server part runs under Windows OS);
- _ 4 – authentication scheme by login and password;
- _ 7 (by default) – all schemes are supported.



When multiple authentication schemes are supported, the setting value is set as a sum of values corresponding to the supported schemes.

3. Specify the settings of provider for server:

- _ If you use OpenSSL in the openssl_pr.ini file in the [TLS Connection Settings] section in the **UsedHandShakeScheme** parameter set up the authentication scheme number. To select both schemes at once (2 and 4), specify 6.
- _ If you use MP specify its settings in the mp_pr.ini file:
 - _ In the [Certificate Stores] section set up certificate storage. For details, see [5.3.2](#).
 - _ In the [TLS Connection Settings] section set up the following settings:
 - _ **UsedHandShakeScheme** – authentication scheme number in correspondence with the rules of authentication schemes compatibility at server and client;
 - _ **CSPUseLocalMachineStore**=0 – the key is located in the current user's storage;
 - _ **CheckRevocation**=0 – the certificate check for revocation is not performed;
 - _ **CSPCertHash** – hash of the server's certificate.

For details about the settings see [5.4.5](#).

4. In QUIK Administrator specify administrator's login:

- _ For authentication by login and password in domain – specify administrator's login in the **Logins for another authorization system** dictionary;
To sign in login can be specified with domain or without it. If domain is specified full correspondence of domain and login is checked. If domain is not specified login is checked for the default domain.
- _ For authentication by login and password – specify administrator's login in user editing dialog box on the **Security** tab.

2.2.3 QUIK Administrator account creation

To create a QUIK Administrator new account and assign a user with administrator's permissions, run QUIK Administrator server part using the **-set-admin-right** launch parameter.

The format:

```
qadminsrv -set-admin-right -instance=[<instance>] -UID=[<UID>] -QUIK-key-  
filename=[<QUIK-key-filename>]
```

where:

- <instance> – database identifier. The database identifiers are listed in [Instances] section of the qadminsrv.ini file. If the QUIK server uses a single DB, then the parameter is not required.



- <UID> – identifier of a user to assign an RSA key. If the parameter is not specified, a new user will be created.
- <QUIK-key-filename> – path and name of the file containing a public key RSA. The relative or absolute path can be specified. If the name and / or path contains spaces, then the value is quoted, for example, for Windows OS: c:\path\to\file\somefile.txk, for Linux OS: /path/to/file/somefile.txk. If the file contains more than one public key RSA, then the first key in the file is used. If the <UID> parameter is specified and there is an RSA key for a user, then this parameter is not required.

Example for Windows OS:

```
qadminsrv -set-admin-right -UID=350 -QUIK-key-filename="c:\path\to\file\somefile.txk"
```

Example for Linux OS:

```
qadminsrv -set-admin-right -UID=350 -QUIK-key-filename=/path/to/file/somefile.txk
```

2.2.4 Working with qadminsrv service on Linux

The qadminsrv service is managed via the systemctl system service. To register the qadminsrv service, a special configuration file with the .service file extension is created. A shortcut is created in the systemd system directory, and the configuration file is located in the directory of the corresponding service. The name of the configuration file corresponds to the name of the service. For example, for the qadminsrv service, a configuration file named qadminsrv.service is created in the /opt/arqasrv/quik/qadminsrv directory.

The service operation is controlled by the following commands on behalf of a user with administrator permissions:

- Get the current status of the service:

```
sudo systemctl status qadminsrv
```

- Start the service:

```
sudo systemctl start qadminsrv
```

- Stop the service:

```
sudo systemctl stop qadminsrv
```



You can start, stop and get the service status using the following scripts: `q_start.sh`, `q_stop.sh` and `q_status.sh`. The scripts should be launched using the `sudo` utility, for example:

```
sudo ./q_start.sh
```

Distribution

The `qadminsrv` service is distributed for installation on computers with Astra Linux OS as a `<install_qadminsrv-xx.xx.xx.run>` file format, where `xx.xx.xx`– product version (hereinafter run file).

The run file is used to install and update services in the system.

The run file supports the following set of launch parameters:

- `-i [<srvname>]`
Install the service with the `<srvname>` name. The `<srvname>` parameter is optional. If it is missing, the default service name is used, that matches the name of the executable file of the service – `qadminsrv`.
Installation of two services with the same name is prohibited.
- `-d <rootdir>`
Launch parameter applied only when installing the service (combined with `-i`) to specify a root directory for installing the service other than the default directory `/opt/arqasrv`.
- `-n <srvusername>`
Launch parameter applied only when installing the service (combined with `-i`) to override the service owner (default username: `arqasrv`) user who will be the owner of the service files and on whose behalf the installed service will run.
- `-u [<srvname>]`
Update the service with the `<srvname>` name. The `<srvname>` parameter is optional. If it is missing, the default service name is used, that matches the name of the executable file of the Access server – `qadminsrv`.
The service location and the name of the server owner user are not required to be specified, as they are stored in `/etc/arqasrv/<srvname>`.
- `-e`
Unpack the full contents of the archive, including configuration ini files. It is unpacked into a subdirectory with a name equal to the name of the run file (without `.run`), which in case of missing is created next to the executable file.
- `-h, -?`
Display a summary of the launch arguments.

Example of executing the run file to install the service:

```
sudo ./install_qadminsrv-xx.xx.xx.run -i qadminsrv -d /opt/customdir
```



Example of executing the run file to update the service:

```
sudo ./install_qadminsrv-xx.xx.xx.run -u qadminsrv
```

Example of executing the run file for unpacking:

```
./install_qadminsrv-xx.xx.xx.run -e
```

Updating service

The service is updated by a user with local administrator rights (root) via the console by calling the run file.

When updating you must specify the service name. If you are updating the service with the default name – qadminsrv, then the name does not need to be specified. Further, we assume that the service with the default name is being updated.

Follow the steps below to update the service:

1. Stop the qadminsrv service from the directory with the installed service by the following command:

```
sudo ./q_stop.sh
```

or from any directory other from the service directory by the following command:

```
sudo /opt/arqasrv/quik/qadminsrv/q_stop.sh
```

2. Copy the install_qadminsrv-xx.xx.xx.run file to the directory that the current user has permissions to operate in, such as the home directory (/home/<user> or ~/).
3. Execute the command to add execution rights to the run file:

```
chmod +x install_qadminsrv-xx.xx.xx.run
```

4. Execute the service update command:

```
sudo ./install_qadminsrv-xx.xx.xx.run -u
```



The current user's password may be required to execute the command.

The following operations will be performed during the execution of the run file:

- Automatic backup is performed. In the /opt/arqasrv/quik/qadminsrv directory where the service is installed, in the .backup subdirectory an qadminsrv_YYYYYY.MM.DD_hh.mm.ss.tar.gz archive will be created, where all files of the updated service will be placed, except for log files and storage files, relevant only within a day.
- The previous files will be replaced with a new set of files in the directory of the service to be updated.
- The **arqasrv** user will be assigned as the owner of all updated files and subdirectories in the service directory.
- Conversion of settings in configuration files will be performed if required.

If the service is successfully updated, the following message is displayed in the console:

"Update of service "qadminsrv" has been successfully completed".

In case of another diagnostic output, please contact the QUIK technical support:

quiksupport@arqatech.com.

Postponed files from previous installations can accumulate, so it is recommended to periodically delete archives from the .backup directory.

Removing service

The service is removed by a user with local administrator rights (root) by calling the uninstall.sh script which is located in the directory of the corresponding service.

Further, we assume that the service with the **qadminsrv** default name is being deleted.

To delete a service, follow these steps:

1. Stop the qadminsrv service from the directory with the installed service by the following command:

```
sudo ./q_stop.sh
```

or from any directory other than the service directory by the following command:

```
sudo /opt/arqasrv/quik/qadminsrv/q_stop.sh
```

2. Run the uninstall.sh command file in the /opt/arqasrv/quik/qadminsrv installed service directory by the following command:




```
sudo ./uninstall.sh
```

or from any directory other than the service directory by the following command:

```
sudo /opt/arqasrv/quik/qadminsrv/uninstall.sh
```

The current user's password may be required to execute the command.

The following operations will be performed as a result of executing the command:

- Service registration with the qadminsrv name in the systemd service management system is deleted.
- The /etc/arqasrv/qadminsrv file, where the parameters of the installed service were recorded, is deleted.
- The /opt/arqasrv/quik/qadminsrv directory where the service is installed is renamed to /opt/arqasrv/quik/qadminsrv.backup_ YYYY.MM.DD_hh.mm.ss. The directory is renamed, not deleted, in case you need data from it. If it is not required, delete the directory manually.

If the service is successfully removed, the following message is displayed in the console:

"Removing of service 'quik' has been successfully completed"

In case of another diagnostic output, please contact the QUIK technical support:

quiksupport@arqatech.com.

2.2.5 Migrating qadminsrv service from Windows to Linux

When migrating software from Windows OS to Astra Linux OS, the following restrictions of the Linux version compared to the Windows version should be considered:

- Only PostgresPRO DBMS is supported for Astra Linux OS. When using the QUIK server database on a DBMS other than the specified one, you must first migrate the database to PostgresPRO. For instructions on database migration to PostgresPRO, please contact QUIK technical support: quiksupport@arqatech.com.
- MP crypto provider is not supported.
- To migrate software running on Windows OS to a computer with Astra Linux OS:
 - The software version that is migrated from Windows OS must be equal to the software version that will be installed on Astra Linux OS.
 - Migration must be performed at non-trading time: after the end of trading and stopping the service and before the start of trading, before the first start of the service.

Before migrating the service from Windows to Linux, it is required to update all used plugins for QUIK Administrator to the versions listed below:

- EES 2.30.100;
- QME Qme\2.2.100;



- InvAdvDistributor 3.11.100;
- Instructions 20.7.100;
- BrokerQuote 4.48.100;
- OMS OMS\6.x\6.2.100;
- POService 1.9.100;
- QuikAuctions 1.1.100;
- QChatGate V_1.14.100;
- QuikREPO 1.2.100;
- SecDescDistributor 3.4.100;
- SMS 3.19.100;
- SOR 4.8.100.

To obtain the corresponding update, please contact QUIK technical support:
quiksupport@argatech.com.

Service migration to Astra Linux OS should be performed by a user with administrative privileges (root).

For Linux OS, conversions must be performed for all migrated files according to the [INI file conversion rules when migrating software from Windows to Linux](#).

To migrate software from Windows OS to Astra Linux OS, follow the steps below:

1. Install the service by following the steps from sub-section [2.2.1](#).
2. Copy the following files from the Windows service directory to the Linux service directory /opt/arqasrv/quik/qadminsrv:
 - _ .ini configuration files;
 - _ .cfg crypto provider configuration files;
 - _ Key files (*.txk), provider certificates catalogs:
 - _ The **seccring.txk**, **pubring.txk** keys to set up the crypto32 crypto provider;
 - _ The **certs** catalog to set up the OpenSSL_pr crypto provider;
 - _ The **signalcom** catalog to set up the Signalcom_pr crypto provider.
3. Convert the names of the files and directories copied in the previous step to lower case. For this, run the command in the /opt/arqasrv/quik/qadminsrv directory:

```
sudo ./postmigration.sh
```

4. Start the qadminsrv service from the service directory with the command:



```
sudo ./q_start.sh
```

or:

```
sudo systemctl start qadminsrv
```

5. Check that the service has been successfully started with the command (from the service directory):

```
sudo ./q_status.sh
```

or:

```
sudo systemctl status qadminsrv
```

In case of problems, please contact QUIK technical support: quiksupport@argatech.com.

2.2.6 QUIK system user registration

1. Run QUIK Administrator.
2. Select the menu item **QUIK server/Organizations**. Add your organization to the dictionary, please fill in all fields.
3. Select the menu item **QUIK server / Users**. Add the account of QUIK system administrator to user's dictionary.

For that select name of your organization in the dictionary, enter initials of the manager and establish authorization's validity period.

List of classes contains names of security classes specified in settings. Choose sequentially each of them and press the **Manager** button to set rights to work with the class.

4. Specify the identifier of the trading participant in trading system in the **Firm code** field (the **Classes permissions** tab in the user edit window). The **Client code on the dealer's side** field is not filled in for manager.
5. Register the user's public key generated during installation of QUIK Server (see [2.2.3](#), item 6), by pressing button **RSA keys**. In the opened window select the key file by pressing button **RSA file**. Load from these the key by pressing button **Add** and then close the window.
6. Similarly, add other users of your system installing the necessary parameters of access to the system using templates rights. Complete the field **Client code on the dealer's side** by the symbolic code that will be subsequently used by manager for setting limits and authentication of users when working with the system.



Detailed description of **QUIK Administrator** work is presented in the Administrator's manual.

QUIK system is ready to work!

Run the QUIK Workstation using the access keys and credentials of your first user.

2.3 QUIK workstation banner configuration

In QUIK workstation, a banner may be displayed on the toolbar, clicking on which opens a website (for example, a broker's website).

2.3.1 Configuration of banner

To configure banner, follow the steps below:

1. Copy a banner image file to the directory **QUIK\Server\Areas\Banners**. The file requirements are:
 - _ file format – .bmp;
 - _ file extension – any. Recommended: 468*60 pixels;
 - _ color depth – 8 bit.
2. In the directory **QUIK\Server\Areas\Banners**, in the **banners.ini** file configure the settings in section [url_set]:
 - _ **url** – URL address.
 - _ **image** – name of the banner image file.

Example:

```
[url_set]
url=http://www.broker-website-example.ru
image=broker.bmp
```

3. On the computer where a QUIK server is run, in the file **QUIK\Server\quik.ini** configure the following settings:

```
[natural_level_section]
module=banner_module
[banner_module]
module=dwbanner.dll
```

The banner settings for the server and the access server are the same

2.3.2 Deactivation of banner

To disable receiving banners from the access server, do the following:



1. Make sure that the following line is present in the [natural_level_section] section in the quik.ini access server settings file:

```
module=banner_module
```

2. Make sure quik.ini file of access server has the following section:

```
[banner_module]
module=dwbanner.dll
```

3. Make sure the default value ("1") of the following key is displayed in the [banner_module] section of quik.ini file of access server:

```
ignore_up_dwell=1
```

```
[banner_module]
module=dwbanner.dll
ignore_up_dwell=1
```

4. Make sure the dwbanner.dll module is present and then start the access server.

After applying such settings, the banner won't be sent from the server to the access server and users of the access server won't see it.

2.3.3 Replacement of banner

To replace the banner, configure the scheme as follows:

1. The .\Areas\Banners\ directory has to contain the .ini file with the settings as following:

```
[url_set]
url=c:\
image=test.bmp
```

where:

- _ Value of the url key — url, that opens in QUIK Workstation;
 - _ image — name of the file in .\Areas\Banners\ directory.
2. Change the old file to new one with the name that differs from the current banner name (for example test2.bmp) in .\Areas\Banners\ directory.
 3. Change the value of the image key to a new one in .ini file — test2.bmp.



URL can be changed without changing the image.

Also, without changing image and url, you can add another .ini file with a different url and image. In this case, the banner from the new .ini file is used.

2.4 File transfer settings


In the QUIK system, you can transfer files from the server to QUIK workstations (via personal file areas to the QUIK server). This makes possible to organize sending of reports to customers, also reports can be signed with digital signature.

To send files to clients that are not intended for updating the QUIK workstation, the files must be placed in the specified directory:

- server\areas\private\ – for sending to specific users.
- server\areas\public\ – for sending to all users.

To place documents and files intended for the employees of the company, you should use the server\areas\company\ directory.

After that, you need to use the **System / Receiving files** dialog box:



3. Running QUIK server

QUIK server is run as a service. Market data, as well as information about orders and trades, is loaded from the repository files and is available to all users connected to the QUIK server.



It allows, for example, unloading information about trades executed on the previous trading day. The data for the previous trading session is cleared when the first trading interface connects to the QUIK server.

The QUIK server can also be run using the [launch parameters](#).

To upload positions to the QUIK server when it starts, copy the prepared .lim file to the computer where the QUIK server is installed. The QUIK server service is started from the command line with the parameters indicating the positions to be loaded from this file. For example:

```
QUIK\Server\q_start.exe -clean -loadlimits <file_with_positions>
```

When the gateways are connected to the QUIK server, the uploaded positions will be displayed in the QUIK Workstation.

If you have any questions, contact QUIK technical support:
quiksupport@argatech.com.

3.1 QUIK server launch parameters

If the configuration file of Limits calculation library is empty or is not available the QUIK server start is interrupted with conclusion of the relevant diagnostic to log file.

3.1.1 -new or /n

Start a QUIK server in the loading mode with new data loading mode in which:

- market data and orders and trades are requested from the trading system,
- client positions are calculated based on the received information considering trades of the current session and position adjustments,
- all files with .ik extension are cleared except the following:
 - news file (news.ik),
 - file of server QPILE portfolios (cstructp.ik),
 - cash positions file (mlimit.ik)
 - instruments positions file (dlimit.ik).



3.1.2 -clean or /c

Start a QUIK server in the loading mode with full cleaning of data as well as cleaning all files with .ik extension.

The key can be used in the combinations that include:

- [-loadlimits](#);
- [-rolling](#) and [-loadlimits](#).

3.1.3 -old or /o

Start a QUIK Server in mode of loading with old data without cleaning storages.

3.1.4 -holiday or /h

Starting a QUIK server in holiday mode on a day that is a working day according to the standard calendar or according to the settings of the [\[trade_date\]](#) section of the quik.ini file.

3.1.5 -workday or /w

Starting a QUIK server in working day mode on a day that is a day off according to the standard calendar or according to the settings of the [\[trade_date\]](#) section of the quik.ini file.

3.1.6 -loadlimits or /l

Start a QUIK server with loading positions from a file. Name of file with positions and its path must be typed in the command line after the key. Field formats of positions to be loaded are given in Appendix (see [5.1](#)). The information of the positions loaded from the file is updated only after connecting the interfaces (trading interfaces or the Holiday Information interface).

The parameter can be used in the combination that includes **-clean** and **-rolling** parameters (see [3.1.14](#)).

3.1.7 -install or /i

Install a QUIK Server as a service of Windows.

3.1.8 -remove or /r

Delete a QUIK Server as a service of Windows.

3.1.9 -removestops or /rs

Start in mode of deleting stop orders from the current QUIK Server.

After the start, users must make stop orders own on any other server so that these orders could trigger.

The parameter **-removestops** can be used together with **-new** and **-clean** parameters.



3.1.10-text or /t

Exporting data of a particular type to a text file.

Format:

```
quik.exe -text [<FILE>] [<TYPE>] [tsv]
```

where:

- <FILE> – exported file with orders and trades.
- <TYPE> – data type. Valid values:
 - _ orders – export orders from file (order.ik);
 - _ trades – export trades from file (trade.ik).

If names of files with orders and trades are different from order.ik and trade.ik, <TYPE> parameter is required.

- tsv – convert file to tsv format.

For example:

```
quik_02.exe -text trade.ik trades tsv > trade.txt
```

3.1.11-removelimits or /rl

Start a QUIK server with cleaning data on client cash and securities positions, and restrictions of accounts at derivatives market. Other data (e.g., orders, trades, data from the Quotes table, etc.) are not deleted. The launch parameter can be used with the **-loadlimits** launch parameter.

3.1.12-rolling or /ro

Start a QUIK server with rolling positions. The information of the transferred positions is updated only after the interfaces (trade interfaces or the Holiday Information interface) are connected.

The launch parameter can be used in the combination that includes **-clean** and **-loadlimits** launch parameters (see [3.1.14](#)).

3.1.13-clean -loadlimits

Start a QUIK server in the loading mode with full cleaning of data as well as cleaning all files with .ik extension and loading positions from file. Positions are recalculated considering trades of the current session but not considering position adjustments during the trading day (adjustments must be made again).



3.1.14-clean -loadlimits -rolling

Start of a QUIK in the loading mode with full cleaning of data as well as cleaning all files with .ik extension. The file that contains positions on the moment of the previous day trading end is used as a source for rolling.

For the field formats of loaded positions, see Appendix (sub-section [5.1](#)).

4. Password encryption

Passwords specified in the Module settings can be encrypted. The password must not begin with "\$" and "#". If you use a password that begins with any of the above symbols, change it.

To activate password encrypting functionality, add "\$" before the password in the configuration file.

For example:

```
Password=$secret
```

When attempting to use a password, the server encrypts the password and saves it to the configuration file in an encrypted form. The encrypted password is marked by "#" symbol at the start of a string.

When transferring the program to another computer or reinstalling the operational system, the encrypted passwords get unavailable for decryption. In this case, the appropriate passwords must be reset.

5. Appendix

5.1 Format of positions

Parameters obligatory for configuration are ticked by "*".

Format of instrument positions:

Parameter	Description	Size, accuracy (in symbols)
* DEPO:	Title of line with expressed instrument position	



Parameter	Description	Size, accuracy (in symbols)
* FIRM_ID	Identifier of trading participant	12
* SECCODE	Instrument code	12
* TRDACCID	Trading account	12
* CLIENT_CODE	Client code	12
* OPEN_LIMIT	Opening limit	30
* OPEN_BALANCE	Client position	30
CURRENT_LIMIT	Current limit	30
WA_POSITION_PRICE	WA position price	30, 6
WA_PRICE_CURRCODE	WA position price currency	4
LIMIT_KIND	Settlement period. Valid values: _ 0 – for current limits; _ <N> – for limits on positions with T+<N>; _ value less than zero – for technological limits; _ <YYYYMMDD> – for limits on positions in calendar days	32, 0

Format of cash position:

Parameter	Description	Size, accuracy (in symbols)
* MONEY:	Title of line with expressed cash position	
* FIRM_ID	Identifier of trading participant	12
* CURR_CODE	Currency code	4
* TAG	Settlement tag	4
* CLIENT_CODE	Client code	12
OPEN_LIMIT	Opening limit	30, 2
* OPEN_BALANCE	Client position	30, 2



Parameter	Description	Size, accuracy (in symbols)
CURRENT_LIMIT	Current limit	30, 2
LIMIT_KIND	Settlement period. Valid values: 0 – for current limits; <N> – for limits on positions with T+<N>; - value less than zero – for technological limits; <YYYYMMDD> – for limits on positions in calendar days	32, 0
* LEVERAGE	Leverage. Valid values: - Non-negative values; -1 – no leverage	30, 2

Example of records in positions file:

```
MONEY: FIRM_ID = NC0038900000; TAG = EQTS; CURR_CODE = SUR ; CLIENT_CODE = 004;
OPEN_BALANCE = -46.52; OPEN_LIMIT = 0.00;
MONEY: FIRM_ID = NC0038900000; TAG = EQTS; CURR_CODE = SUR ; CLIENT_CODE = 004;
OPEN_BALANCE = -46.52; LEVERAGE = -1;
MONEY: FIRM_ID = NC0038900000; TAG = EQTV; CURR_CODE = SUR ; CLIENT_CODE = 004;
OPEN_BALANCE = 1048.51; OPEN_LIMIT = 450000.00; LIMIT_KIND = 1;
DEPO: FIRM_ID = NC0038900000; SECCODE = HYDR; CLIENT_CODE =10004/10004; OPEN_BALANCE
= 113955; OPEN_LIMIT = 0; TRDACCID = L01-00000F00;
DEPO: FIRM_ID = NC0038900000; SECCODE = IRAO-004D; CLIENT_CODE =10006/10006;
OPEN_BALANCE = 738467; OPEN_LIMIT = 0; TRDACCID = L01-00000F00; LIMIT_KIND = 1;
```

5.2 INI file conversion rules when migrating software from Windows to Linux

The following conversions are required for files and paths:

- File names and paths must be in lower case.
- All mentions of dynamic libraries (*.dll) must be converted to the corresponding name on Linux. For this, the prefix "lib" is added to the name and the extension is replaced by *.so, for example:

```
module=openssl_pr.dll
replace by:
module=libopenssl_pr.so
```

- Path delimiters – backslash "\" should be replaced by a forward slash "/".



Settings that contain paths to files located on the QUIK server should be changed so that the path is correct in Linux semantics.

If the QUIK server is installed on a separate computer, it is required to connect the network resource by a command on behalf of a privileged user (root), it is necessary to have an installed cifs-utils package included in the AstraLinux distribution kit.

For example, the QuikIni configuration of the [DealerLibraryOptions] section for Windows is as follows:

```
[DealerLibraryOptions]
QuikIni=\\QUIKSERVER\DRIVE_D\QUIK1\Server\quik.ini
```

The resource DRIVE_D is available on the computer where the QUIK server with the QUIKSERVER network name is installed.

Connection of a network resource is performed with the command:

```
sudo mount.cifs //QUIKSERVER/DRIVE_D/ /mnt/q1/ -o uid=arqasrv,user=winuser
```

Where:

- QUIKSERVER – computer name where the QUIK server is installed;
- DRIVE_D – network resource name;
- /mnt/q1/ – network disk connection path (the directory must exist);
- arqasrv – Linux user on behalf of whom the QUIK Administrator service is launched;
- winuser – Windows user who is allowed to connect to the network resource.

After connecting the network resource, the configuration is as follows (the path is case sensitive):

```
[DealerLibraryOptions]
QuikIni=/mnt/q1/QUIK1/Server/quik.ini
```

The Limits Calculation Library files listed in the [dealer-library] section must be available for recording by the user on whose behalf the network resource is connected.

For more information about connecting network resources in Linux, please contact your system administrator.



5.3 OpenSSL encryption configuration file format

In the OpenSSL_Pr.ini file the settings of encryption by OpenSSL cryptographic library is configured (www.openssl.org). OpenSSL application does not require saving certificates in OS register on the platform with the QUIK server. It makes certificate installation and servicing easier.

5.3.1 [General] section

- **CertStoreFile** – certificate storage file name. Value by default: certs\store.pem.
- **ServerCertificateKey** – password of server's certificate key. The password can be encrypted (see 4).
- **NewServerCertHash** – new server's certificate hash.
- **NewServerCertDomainName** – new server's certificate domain.

NewServerCertHash and NewServerCertDomainName settings specify the parameters of a new certificate when planned certificate replacing at the server. After certificate replacement the values of NewServerCertHash and NewServerCertDomainName settings are recorded to ServerCertHash and ServerCertDomainName parameters of OpenSSL_Pr.ini file in the QUIK Workstation.

- **ClientCertificatesDir** – path to the directory that contains certificates for checking digital signature. Value by default: certs\client.

5.3.2 [TLS Connection Settings] section

The following connection parameters are specified in the section:

- **ServerHandShakeScheme** – the supported authentication scheme. Possible values:
 - _ 1 – authentication by certificate;
 - _ 2 – authentication in domain;
 - _ 4 – authentication by login and password;
 - _ 7 (by default) – all the schemes are supported besides 8 (password recovery);
 - _ 8 – password recovery;
 - _ 32 – authentication within the domain (by domain name of the user).

When a few authentication schemes are supported, the specified value of the field is the sum of values, corresponding to the supported schemes.

- **UsedHandShakeSchemePrefer** – the preferred authentication scheme. It must be selected if a client had chosen scheme 0 (is defined by server). Possible values:
 - _ 1 – authentication by certificate;
 - _ 2 – authentication in domain;
 - _ 4 (by default) – authentication by login and password.



- **SSLProtocols** – the list of TLS protocol versions available for connection, separated by a comma. Possible values:
 - _ TLSv1.0;
 - _ TLSv1.1;
 - _ TLSv1.2.
- **CA** – path to the directory that contains root certificates. Value by default: certs\CA.
- **CRL** – path to the directory that contains certificate revocation lists. Value by default: certs\CRL.

5.4 MP encryption configuration file format

The file specifies the encryption settings using the MP cryptography library:

- on the QUIK server side – in the MP_Pr_server.ini file;
- on the client side — in the MP_Pr_client.ini file.

5.4.1 [Crypto Provider Settings] section

The section contains description of the cryptographic provider settings required for check of a digital signature.

To use the digital signature, specify a key container using any of the following methods:

1. Specify parameters of the container:

- _ **CSPName** – name of a Cryptographic Service Provider (CSP) used by the certificate.
- _ **CSPContainerName** – name of the key container.
- _ **CSPTYPE** – CSP provider type.

If CSPName parameter is not specified, the system provides a CSP provider, assigned by default for a specified type of cryptographic provider.

2. Specify a file of the certificate linked to the key container:

- _ **CSPCertFileName** – path to the certificate file.

3. Specify a hash of the certificate linked to the key container:

- _ **CSPCertHash** – hash of the installed certificate.

To get a certificate hash:

- _ Open the certificate file;
- _ Switch to the **Details** tab;
- _ Copy the value of the **Thumbprint** field and remove the spaces.

Additional parameters to set up the digital signature (optional):



- **CSPUseInService** – indicates that cryptographic provider works in 'silent' mode. Possible values:
 - _ 0 – cryptographic provider works online;
 - _ 1 – cryptographic provider works in 'silent' mode.

The cryptographic provider doesn't interact with the user in 'silent' mode. An error appears upon the occurrence of an event that requires interactive communication (for example, entry of the password to access the container).
- **CachKeyAndCertificates** – indicates that keys and certificates are cached for quick access to them. Possible values:
 - _ 0 – do not cache;
 - _ 1 – cache.
- **CSPUseLocalMachineStore** – private key location. Possible values:
 - _ 0 (by default) – the key is located in the current user's storage;
 - _ 1 – the key is located in the local computer store.
- **CheckRevocation** – indicates that the certificate is checked for revocation. Possible values:
 - _ 0 – the check is not performed;
 - _ 1 – the check is performed.
- **UseLocalCA** – attribute for using the local certificate storage. Possible values:
 - _ 0 – local storage is not used.
 - _ 1 (default) – local storage is used.
- **CA** – path to the local CA certificate storage. Default value: Certs\CA.
- **CRL** – path to the local certificate revocation list (CRL) storage. Default value: Certs\CRL.

5.4.2 [Certificate Stores] section

The section contains description of the certificates store, where the certificates are searched to set up the encryption modes and digital signature:

At least one certificate storage should be specified to ensure correct work of the cryptographic provider.

- **MY** – attribute of standard personal storage of the user certificates. Possible values:
 - _ 0 – not used;
 - _ 1 – used.
- **CA** – attribute of standard storage of the Certification Authorities' certificates. Possible values:
 - _ 0 – not used;
 - _ 1 – used.



- **ROOT** – attribute of standard root storage. Possible values:
 - _ 0 – not used;
 - _ 1 – used.
- **SPC** – attribute of standard storage of the software vendors' certificates. Possible values:
 - _ 0 – not used;
 - _ 1 – used.
- **CUSTOM_STORE** – attribute of third-party external storage. Possible values:
 - _ 0 – not used;
 - _ 1 – used.
- **CUSTOM_DIR** – attribute of directory for storing certificates. Possible values:
 - _ 0 – not used;
 - _ 1 – used.

Each store is described by the separate section of the [<storage>] view (see [5.4.3](#) sub-section).

5.4.3 [<storage>] section

- **HOST** – host where the store is located. Value: "." (full stop).
- **LOCATION** – physical store location.
- **TYPE** – store type. Possible values:
 - _ 1 – system store;
 - _ 2 – external storage located in a specific file;
 - _ 3 – directory with certificate files.
- **UPDATABLE** – feature of an updatable store. Possible values:
 - _ 0 – not allowed to be updated;
 - _ 1 – allowed to be updated.
- **PRIORITY** – priority. Value: 1.

For example:

```
[CUSTOM_STORE]
HOST=.
LOCATION=D:\QUIK\Server\CPStorage\usercerts.sto
TYPE=2
UPDATABLE=1
PRIORITY=1
```

5.4.4 [TLS Connection Settings] section

The section is used to configure a TLS connection.



- **SSLProtocols** – list of the protocols used (separated by commas). Possible values:
 - _ TLSv1;
 - _ TLSv1.1;
 - _ TLSv1.2 (by default).

To work in encryption mode, specify a private key. To do this, specify a certificate linked to a private key by using one of the following methods:

1. Specify parameters of the container:

- _ **CSPName** – name of a Cryptographic Service Provider (CSP) used by the certificate;
- _ **CSPContainerName** – name of the key container;
- _ **CSPTYPE** – CSP provider type.

If CSPName parameter is not specified, the system provides a CSP provider, assigned by default for a specified type of cryptographic provider.

2. Specify a file of the certificate:

- _ **CSPCertFileName** – path and name of the certificate file.

3. Specify a hash of the certificate linked to the key container:

- _ **CSPCertHash** – hash of the certificate.

Authentication parameters:

- **UsedHandShakeScheme** – authentication scheme used. Possible values:

- _ 1 * – authentication by certificate, i.e. the client is checked by certificate that he provided establishing an SSL/TLS connection;
- _ 2 * – authentication by domain login and password through the Domain Controller;

The scheme 2 cannot be used, if in the QUIK Administrator's server configuration file in the [QuikOptions] section the EnableMultiple2FaLogins setting contains '1'.

- _ 4 * – authentication scheme by login and password;
- _ 7 (by default) – all schemes are supported, except for 8 (password recovery);
- _ 8 – password recovery.
- _ 32 * – authentication within the domain (by domain name of the user).

When multiple authentication schemes are supported, the setting value is set as a sum of values corresponding to the supported schemes.

(*) Server's and client's authentication schemes compatibility:

- 1. If the authentication scheme number 1 is configured on the server, the client can use the first and fourth schemes.**



2. If the authentication scheme number 2 is configured on the server, the client can use the second and fourth schemes.
3. If the authentication scheme number 4 is configured on the server, the client can use only the fourth scheme.
4. If the authentication scheme number 32 is configured on the server, the client can use only the scheme number 32.

- **DomainController** – address of the Domain Controller being referenced when authenticating a client. This parameter is used if the authentication scheme number 2 is applied.

If the DomainController setting is not specified, the current Domain Controller is used.

- **DomainLogin** ^{*} – user's domain login for the access server authentication. Value by default: "" (empty).
- **DomainPasswd** ^{*} – user's domain password for the access server authentication. Value by default: "" (empty).

(^{*}): These parameters are used only when connected via the access server where the authentication scheme number 2 is configured.

Additional parameters to set up the encryption mode (optional):

- **CSPUseInService** – indicates that cryptographic provider works in 'silent' mode. Possible values:
 - _ 0 – cryptographic provider works online;
 - _ 1 – cryptographic provider works in 'silent' mode.

The cryptographic provider doesn't interact with the user in 'silent' mode. An error appears upon the occurrence of an event that requires interactive communication (for example, entry of the password to access the container).

- **CSPUseLocalMachineStore** – private key location. Possible values:
 - _ 0 (by default) – the key is located in the current user store;
 - _ 1 – the key is located in the local computer store.
- **CheckRevocation** – indicates that the certificate is checked on the revoked certificates list by the cryptographic provider. Possible values:
 - _ 0 – the check is not performed;
 - _ 1 – the check is performed.



- **IOBufferMaxSize** – buffer size (in bites) for input/output data in TLS connection handshake. Value by default: 65536.
- **CheckClientCert** – indicates that the client's certificate is verified using the additional tools of Windows operating system.
- **HashCalcCount** – number of iterations of the password hash function calculation on the server. Possible values: from 1 to 10037. Value by default: 4999.

When using authentication within a domain (**UsedHandShakeScheme**=32), the following settings are additionally specified in the MP_Pr_client.ini client file:

- **SecurityPackage** — authentication protocol within a domain. Possible values:
 - _ Kerberos (default);
 - _ NTLM.
- **ServerSPN** – Service Provider Name (SPN) identifier of the QUIK server in the Active Directory account. Used when **SecurityPackage** is set to **Kerberos**.

To find out the SPN, run the "setspn -l <name of the domain account under which the server is running>" command from the command line or contact your administrator.

5.4.5 [TLS Extra Parameters] section

The section contains the settings (optional) for the planned change of server's certificates.

The settings of the planned change of certificate should be specified before the expiration date of the current certificate. The settings are deleted after the certificate change.

- **NewServerCertHash** – possible values:
 - _ Hash of a new server's certificate – after the certificate change, this value is written to the **ServerCertHash** setting of the **MP_Pr_client.ini** client's file and then the value of the **NewServerCertHash** setting is deleted.
 - _ DELETE – cancellation of the certificate change procedure.

Value by default: "" (empty).

- **NewServerCertDomainName** – possible values:
 - _ Domain name of a new certificate – after the certificate change, this value is written to the **ServerCertDomainName** setting of the **MP_Pr_client.ini** client's file and then the value of the **NewServerCertDomainName** setting is deleted.
 - _ DELETE – cancellation of the certificate change procedure.

Value by default: "" (empty).



5.5 Daily maintenance of QUIK server

5.5.1 Service start and stop

If you have any questions, please contact QUIK technical support:
quiksupport@argatech.com.

A QUIK server and interfaces to trading systems must be restarted daily because the trading venues are restarted daily.

If there is no schedule of service restart, the current trading session date can be determined incorrectly thus resulting in connection problems of trading interfaces. Services should be stopped after trading in corresponding venues is over, and started in the morning before trading starts.

The service start schedule must be set according to the [ClearingTime](#) setting value in section [trade_date] of the quik.ini configuration file, which must correspond to the time when a service is stopped. For example, if a QUIK server stops at 2:30 AM and starts at 5:30 AM, then the value can be set as follows:

```
[trade_date]
ClearingTime=040000
```

The **ClearingTime** setting can be also set in the settings of other services and modules of the QUIK system. For more information, see Administrator's manual of these modules.

A QUIK server can be started [with](#) or [without](#) keys.

Recommended schedule

Time	Event
Before 5:30 AM	QUIK server start (QuikServer service)
5:35 AM	Start the Cross currency rates forming module (CrossRateTW)
5:40 AM	Start the Replicator (ReplTW)
5:45 AM	Start the Alert dispatch module (SMS)
5:47 AM	Start access servers and web2QUIK modules
5:50 AM	Start the MOEX gateways AstsBridge or DFServer (Securities, FX, clearing system)
5:53 AM	Start the SPECTRA trading system gateway of the MOEX Derivatives market (SpectraCGate)



Time	Event
5:55 AM	Start the Moscow Exchange FX Market trading interface (AstsCurrGate) and Moscow Exchange Clearing System of the FX Market program interface (AstsCurrRiskGate)
5:57 AM	Start the Moscow Exchange Securities Market trading interface (AstsGate) and Moscow Exchange Clearing System of the Securities Market program interface (AstsRiskGate)
6:00 AM	Start the Moscow Exchange Derivatives Market trading interface (FortsGate)
6:10 AM	Start the SPB Exchange trading interface (SpbExchangeGate)
8:55 AM	Start the MOEX gateways AstsBridge or DFServer (money market)
9:05 AM	Start the MOEX Money market trading interface (AstsGKO)
9:05 PM	Stop the MOEX Money market trading interface (AstsGKO)
9:10 PM	Stop the MOEX gateways AstsBridge, DFServer (money market)
0:00 AM	Stop the Moscow Exchange Securities Market trading interface (AstsGate), Moscow Exchange FX Market trading interface (AstsCurrGate), Moscow Exchange Clearing System of the Securities Market program interface (AstsRiskGate) and Moscow Exchange Clearing System of the FX Market program interface (AstsCurrRiskGate)
0:00 AM	Stop the Moscow Exchange Derivatives Market trading interface (FortsGate)
0:10 AM	Stop the MOEX gateways AstsBridge, DFServer (Securities, FX, clearing system)
0:10 AM	Stop the SPECTRA trading system gateway of the MOEX Derivatives market (SpectraCGate)
2:20 AM	Stop the SPB Exchange trading interface (SpbExchangeGate)
2:25 AM	Stop the Cross currency rates forming module (CrossRateTW)
2:25 AM	Stop access servers and web2QUIK modules
2:27 AM	Stop the Alert dispatch module (SMS)
2:27 AM	Stop the Replicator (ReplTW)
2:30 AM	Stop the QUIK server (QuikServer service)

Running QUIK server without keys

When running QUIK server without keys, it loads market data and orders and trades from storage files. This information is available to all users connected to a QUIK server thus allowing to load



information about trades of the previous day in the morning. The previous trading session data is cleared at the moment when the first trading interface connects to a QUIK server.

5.5.2 Client position loading

Client positions must be loaded to a QUIK server daily before the trading starts because positions are not moved to the next day, and all related information is deleted when restarting a QUIK server.

In most cases, positions are loaded using the *.lim file in which each string contains information about one position of a client. This file can be obtained using one of the following ways:

- From a QUIK workstation with manager permissions after the previous trading day is over – select **Dealer / Save positions to file**.
- Using the Program of loading limits to QUIK Server [FillLimits](#).
- From the accounting system of a brokerage company or a bank (recommended).

Positions can be loaded to a QUIK server using one of the following ways:

- [Starting a QUIK server](#) with the key -loadlimits.
- In the Program of loading limits to QUIK Server [FillLimits](#).
- In [QMonitor](#) program.
- Manually from [a QUIK workstation](#).
- Using the Position management program interface QuikLimit.

Starting QUIK server using key -loadlimits

This method is recommended as the fastest one.

1. Copy previously prepared *.lim file to the directory available to a QUIK server.
2. Start a QUIK server with parameters **-clean -loadlimits <path to positions file>**. For example:

```
sc start QuikServer -clean -loadlimits C:\QUIK\limits.lim
```

The key [-new](#) can be used instead of the key [-clean](#) except when incorrect cash and instrument positions were loaded to a server thus requiring loading a correct positions file.

For details, see [3.1.13](#).

Program of loading limits to QUIK server FillLimits

The program connects to a QUIK server a user but start of the program can be automated using the files *.bat or *.cmd that can start it by schedule. The program must be started after trading interfaces are connected and all required instruments are loaded to a QUIK server.



QMonitor program

This method is used if the positions file was not created in time and has to be loaded after starting a QUIK server.

1. Specify the path to the positions file in the server configuration file quik.ini:

```
[ctl_module]
loadlimits_file=C:\QUIK\Server\positions.lim
```

If this setting is not set, positions will be loaded from the file qmonitor.lim that must be located in the QUIK server directory.

2. In the QMonitor program, select **Actions / Load limits from file** to load positions.

QUIK workstation

A positions file can be loaded from a QUIK workstation with manager permissions by selecting **Dealer / Save positions to file**.

The disadvantages of this method are:

- this operation is performed manually by a manager,
- positions can be loaded only after trading interfaces are connected the list of available instruments is received.

Holiday Market Data interface

The interface can be used to load static information to the QUIK server on non-trading days. For example, if clients trade in Western markets via the QUIK system, such a need arises on days that are holidays in the Russian Federation but workdays in the West. The interface allows loading the following information to a QUIK server:

- description of instruments in a separate trading mode and prices to evaluate client positions value;
- information on derivatives instruments, positions, and limits by client accounts for clients who use the Unified cash position module.

5.5.3 Backup files creation

A QUIK server does not store files in system directories and neither write settings into the Windows registry. The files necessary the server functioning are stored in the directory where the QUIK server is installed.

To ensure that you do not lose important files it is recommended that:

- the QUIK server directory be backed up before updating to a newer version,
- the following files be packed up after the trading is over:
 - _ QUIK\AstsGate\AstsGate.ini;
 - _ QUIK\AstsGate\Desc\MoexSpot.data;



- QUIK\QAdmin\Server\MainBase.ini;
- QUIK\QAdmin\Server\QAdminSrv.ini;
- QUIK\QAdmin\Client\QAdmin.ini;
- QUIK\Server*.ini.

as well as other *.ini configuration files of all installed trading and market data interfaces.

- log files of a QUIK server (events.log, deallib.log), interfaces, and modules for the last 10 days be stored. It is also advisable to save *.ik files of a QUIK server.

Built-in log rotation functionality of a QUIK server and other modules can also be used.

It is also recommended to schedule backups for all used databases to run automatically after hours and initiate the reindex procedure on a weekly basis on weekends.

5.5.4 Local time synchronization

Synchronization of local time with the time server on the machines where QUIK server services are installed must be made at a time when all QUIK server services are stopped and no more than once a day.

5.5.5 Recovery after system failure

If a system failure occurs during the trading, please contact QUIK technical support: quiksupport@argatech.com.

Failure of the system software or equipment where a QUIK server is installed may result in problems saving data to file storages and failure running a QUIK server.

General order of service start and stop

1. Stop of interfaces/modules connected to a QUIK server.

The following services **must** be stopped:

- Asts* interfaces (for example: Moscow Exchange Securities Market (Main Market Sector) trading interface (AstsGate), Moscow Exchange FX Market trading interface (AstsCurrGate), Moscow Exchange Clearing System of the Securities Market program interface (AstsRiskGate), Moscow Exchange Clearing System of the FX Market program interface (AstsCurrRiskGate).
- Moscow Exchange Derivatives Market trading interface (FortsGate).
- Broker quotation system.
- Multi-broker service module (Multihub) (if included in a configuration).

The need to stop these services **depends on the conditions**:

- SPB Exchange trading interface (Foreign securities market) (SpbExchangeGate), SPB Exchange trading interface (Russian securities market) (SpbExchangeRuGate) – must be stopped **only in case of a failure** in the SPB Exchange trading system due to which incorrect information was loaded to a QUIK server.

No stopping is required for the following services:



- Client applications.
 - Service applications (for example, an access server, the Market Data Export module, the FIX adapter program interface).
 - Exception: Q2Q service (see [specifics](#)).
2. Stop of a QUIK server.
 3. Start of a QUIK server with the key [-clean](#) (can be combined with [-loadlimits](#)) or [-new](#).
 4. Start of interfaces/modules included into a configuration and used together with one of the stopped interfaces/modules).

The recommended time interval between launch of trading interfaces is 1 to 3 minutes.

Asts* interfaces, SPB Exchange trading interface (Foreign securities market) and SPB Exchange trading interface (Russian securities market) are started **only using** the key [-clean](#).

The specifics of Moscow Exchange Derivatives Market trading interface (FortsGate) start see [below](#).

Start with keys -new and -clean

A QUIK server can be started using the key **-new** or **-clean** in the following cases:

- when updating a QUIK server (**-new** or **-clean**);
- incorrect data was loaded to a server (for example, due to an exchange failure or violation of the QUIK services start procedure):
 - except positions or news (**-new**);
 - including positions in cash and instruments (**-clean**).
- a system failure (lack of disk space, a hardware problem, sudden power outages) resulted in file storage damage:
 - except storages of positions or news (**-new**);
 - including storages of positions or news (**-clean**).

In this case a server will not run, and the type of a corrupted storage will be saved to the events.log file of a QUIK server

For the events.log file analysis, contact QUIK technical support:
quiksupport@argatech.com.

Q2Q service stop and start

The order of stopping and starting services when using the Q2Q service differs from the [General order](#) and looks as follows:

1. Stop a master server.
2. Start a master server with the key [-new](#) or [-clean](#).



3. Stop the Q2Q service and interfaces/modules (see Step 1 of the [General order](#)).
4. Stop a slave server.
5. Start a slave server with the key [-new](#) or [-clean](#).
6. Start the Q2Q service and interfaces/modules (see Step 4 of the [General order](#)).

Start of Moscow Exchange Derivatives Market trading interface

During the day trading session clients submit orders that are moved to the evening session when the main clearing ends. Other orders are cancelled by the trading system. The Moscow Exchange Derivatives Market trading interface (FortsGate) analyses a session status and cancels orders with lifetime limited to the current session once the evening clearing starts.

If a failure occurs during the main trading session, and a QUIK server is started with the key **-new** or **-clean** after the start of the evening session on the Derivatives market (after 7 PM Moscow Time), then the Interface must be started using the key combination **-new -send_esp** to load orders and trades of the main trading session as well as the incoming positions to a QUIK server for the correct operation of the Unified cash position module.

5.6 List of QUIK server error codes

Decimal

error code Error text in the interface in English

8637216	No right to trade in this instrument
8637217	Order price should be positive
8637218	Order price <Value3> is out of set interval from <Value1> to <Value2>
8637219	You have no position for this instrument
8637220	Position for the instrument is exceeded
8637221	Error in changing position for the instrument
8637222	Incorrect name of financial instrument
8637223	Market order for the client account is forbidden
8637224	Money-position for the client is missed
8637225	No right for this trading account
8637226	Money-position is exceeded
8637227	Error while changing money-position
8637231	Securities amount exceed tolerable one
8637232	Close period order is forbidden
8637233	Order depth should be positive



Decimal error code	Error text in the interface in English
8637236	Orders for this trading account and financial instrument are prohibited
8637237	Common limit is exceeded
8637238	Operations on this client code are prohibited
8637239	Maximum limit is exceeded
8637240	Security is restricted for short operation
8637242	Minimal level of client assets
8637243	Operations are not allowed for the specified counterparty
8637244	Operations are not allowed for the specified settlement code
8637245	Initial margin of contract is undefined
8637247	The order value cannot be less than <Value1>
8637248	Order volume is out of range
8637249	Total limit for collateral securities exceeded
8637250	Low discount for the selected security must not be smaller than the initial discount by more than <Value1>
8637251	High discount for the selected security must not exceed the initial discount by more than <Value1>
8637252	The order volume <Value1> exceeds the limit in <Value2> from the average daily turnover <Value3>.
8637253	Operations in <Value1> class with the specified parameters are not allowed.
8637254	REPO transactions on <Value1> of the specified direction and/or REPO term are prohibited
8637255	Operations with <Value1> instrument are prohibited
8637256	Placing a market order to sell <Value1> in <Value2> class is prohibited
8637257	Placing a market short order to sell <Value1> in <Value2> class is prohibited
8637258	Maximum order value <Value1> exceeded

Decimal error code	Error text in the interface in English
8637259	An order can lead to an unacceptable long position size <Value1> in <Value2> (max. position <Value3>)
8637260	An order can lead to an unacceptable short position size <Value1> in <Value2> (max. position <Value3>)
8637261	Maximum transactions quantity <Value1> on interval <Value2> exceeded
8637262	The order quantity must not exceed <Value1>
8637263	The order quantity cannot be less than <Value1>
8637264	The order price cannot be higher than <Value1>
8637265	The order price cannot be lower than <Value1>
8637266	The corrected RCS1 <Value1> is less than 0
8637267	The corrected RCS1 is less than 0. The short position in non-liquid instrument.
8637268	Security of settle currency is not found
8637269	The operation is not allowed. CFI code is not valid.
8637270	Short position <Value1> in <Value2> less liabilities
8637271	Operation is prohibited due to a short in the option <Value1>. Only position closing is allowed.
8637272	REPO trades with a term that includes the record date for coupon payment are not allowed for the class <Value1>
8637319	The order price must be lower than <Value1>
8637320	The order price must be higher than <Value1>
8637326	The maximum size of liabilities was exceeded by <Value1> <Value2>
8637336	Operations are prohibited
8637337	Operations with <Value1> instruments are prohibited
8637338	Operations with settlement date <Value1> or greater are prohibited
8637339	Operations with settlement date <Value1> or greater are prohibited for <Value2> instruments

Decimal error code	Error text in the interface in English
8637340	You cannot enter an order for <Value1>. The instrument ISIN code is not allowed
8637341	You cannot enter an order for instrument <Value1>. Operations with <Value2> are available for unqualified investors successfully tested on complex financial product type <Value3>
8637342	The limit is exceeded for the period <Value1> by <Value2> <Value3>
8637343	Insufficient funds to deposit
8637346	Buy operations are prohibited
8637347	Sell operations are prohibited
8637348	Buy operations are prohibited for <Value1> instruments
8637349	Sell operations are prohibited for <Value1> instruments
8637350	Buy operations with settlement date <Value1> or greater are prohibited
8637351	Sell operations with settlement date <Value1> or greater are prohibited
8637352	Buy operations with settlement date <Value1> or greater are prohibited for <Value2> instruments
8637353	Sell operations with settlement date <Value1> or greater are prohibited for <Value2> instruments
8637354	The available quantity of <Value1> is not sufficient to enter an order
8637355	Error while receiving a futures limit for securities.
8637356	Error while receiving a futures limit for cash.
8637357	Error while setting securities limit.
8637358	Error while setting cash limit.
8637359	Incorrect use of spot asset in the Portfolio initial margin.